STANDARD CONDITIONS OF APPROVAL AND MITIGATION MONITORING AND REPORTING PROGRAM

This Standard Conditions of Approval and Mitigation Monitoring and Reporting Program (SCA/MMRP) is based on the Initial Study/Addendum (IS/A) prepared for the 2012 OARB Project. This revised version of the SCA.MMRP was approved by the City Council on July 16, 2013 and supersedes the previous version (dated October 15, 2012).¹

This SCA/MMRP is in compliance with Section 15097 of the CEQA Guidelines, which requires that the Lead Agency "adopt a program for monitoring or reporting on the revisions which it has required in the project and the measures it has imposed to mitigate or avoid significant environmental effects." The SCA/MMRP lists mitigation measures recommended in the IS/A and identifies mitigation monitoring requirements, as well as the City's Standard Conditions of Approval identified in the IS/A as measures that would minimize potential adverse effects that could result from implementation of the project, to ensure the conditions are implemented and monitored. In addition, "recommended measures," not required by CEQA are also included in this SCA/MMRP.

All mitigation measures, Standard Conditions of Approval, and recommended measures identified in the 2012 OARB IS/A are included herein. To the extent that there is any inconsistency between the SCA and Mitigation Measures, the more restrictive conditions shall govern; to the extent any mitigation measures, recommended measures and/or Standard Conditions of Approval identified in the 2012 OARB IS/A were inadvertently omitted, they are automatically incorporated herein by reference.

Mitigation measures from the 2002 EIR that are applicable to the 2012 OARB Project retain the same numbering; each new mitigation measures is numbered according to the section of the IS/A from which it is derived. For example, Mitigation Measure 3.16-1 is the first new mitigation measure identified in the Section 3.16 Traffic and Transportation of the IS/A. The Standard Conditions are identified with the prefix SCA- followed by an abbreviation of the environmental topic to which is applies (e.g., SCA AES-1 is the first SCA relating to aesthetic impacts).

- The first column indicates the environmental impact as identified in the 2002 EIR and the 2012 IS/A;
- The second column identifies the Standard Condition of Approval (SCA), mitigation measure (MM) or recommended measure applicable to that impact in the 2002 EIR and the 2012 IS/A;
- The third column identifies the monitoring schedule or timing applicable to the 2012 Project; and
- The fourth column names the party responsible for monitoring the required action for the 2012 Project.²

¹ The following mitigation measures were added to the SCA/MMRP by the City Council on July 16, 2013: Mitigation 4.4-3b (West Gateway Rail and Maritime Emissions Reduction Program); Mitigation PO-1 (Stakeholder Review of Air Quality and Trucking Plans); and Mitigation 4.3-10 (Parking Demand Study). No other changes were made to the previous version (dated October 15, 2012).

² At various places throughout the IS/A, mitigation measures and standard conditions of approval indicate that the project sponsor, project applicant, developer, City and/or Port are responsible for implementation. Regardless of such, the City within its jurisdiction and the Port within its jurisdiction are responsible for implementing the mitigation measures and/or standard conditions of approval. Where both the City and Port jurisdictions are involved, both entities are responsible. The Port will impose the City of Oakland SCAs where the 2012 Project requires building and electrical permits, which apply to most projects at the Port. The Port Engineering Department shall review as appropriate any mitigations and SCAs for components of the Project that occur within the Port's jurisdiction.

7SGSW and 7SGSE

7SGSW and FITS

7SGSE and FITS

FITS

7SGSW

7SGSE

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Antigution Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
Aesthetics, Wind and Shad	ows				
Would the project create a new source of substantial light or glare which would adversely affect daytime or nighttime views in the area?	SCA-AES-1: Lighting Plan: The proposed lighting fixtures shall be adequately shielded to a point below the light bulb and reflector and that prevent unnecessary glare onto adjacent properties. Plans shall be submitted to the Planning and Zoning Division and the Electrical Services Division of the Public Works Agency for review and approval. All lighting shall be architecturally integrated into the site.	Prior to the issuance of an electrical or building permit.	City/Port	7SGSW 7SGSE FITS	Applies to design phase only. Applies to all projects as an SCA CEQA mitigation.
	Mitigation 4.11-1 : New lighting shall be designed to minimize off-site light spillage; "stadium" style lighting shall be prohibited.	Prior to the	City/Port	7SGSW 7SGSE	Applies to design phase only.
	Modern security lighting is available that directs light toward a specific site, and substantially reduces spillage of light onto adjacent properties. The City and the Port shall require the use of such directional lighting as a condition of approval for redevelopment projects throughout the project area. In no case shall the City and the Port allow the use of stadium-style lighting, which directs light outward across a broad area.	issuance of an electrical or building permit.		FITS	Applies to all projects as an SCA CEQA mitigation.
2. Would the project introduce structures or	Mitigation 4.11-3: New active or passive solar systems within or adjacent to the project area shall be set back from the property line a minimum of 25 feet.	Prior to the issuance of an electrical or building permit.	City/Port	N/A	Substantial shadows on solar collectors not applicable.
landscape that would now or in the future cast substantial shadow on existing solar collectors (in conflict with California Public	Through design review, the City shall ensure that proposed solar systems are not located in a manner that would unduly restrict design of future development. Such conflicts are to be resolved in design review. If the proposed solar system cannot be designed to accommodate adjacent actions, it shall be disallowed.				(7SGSW and 7SGSE VIA, May 2018 and FITS Minor VIA, July 2018).
Resources Code §§ 25980-25986),	Mitigation 4.11-4: New construction within the Gateway development area adjacent to a parcel containing permitted or existing active or passive solar	Prior to the issuance of an	City	N/A	Substantial shadows on solar collectors not applicable.
photovoltaic cells, or impair the function of a	systems shall demonstrate through design review that the proposed structures shall not substantially impair operation of existing solar systems.	electrical or building permit.			(7SGSW and 7SGSE VIA, May 2018 and FITS Minor VIA, July 2018).
building using passive solar heat collection?	Through design review, the City shall ensure that the effectiveness an operation of existing or permitted active or passive solar systems shall not be substantially impaired. The design of the subsequent proposed structures shall be modified so as not to have such an adverse effect.				
	Mitigation 4.11-5: The City and Port shall coordinate with respect to the design of new, permanent buildings constructed along the Port/Gateway boundary to minimize conflicts over solar access.	Prior to the issuance of an electrical or	City/Port	N/A	Substantial shadows on solar collectors not applicable. (7SGSW and 7SGSE VIA, May 2018 and
	The City and Port shall coordinate with one another regarding design of subsequent redevelopment activities within their respective jurisdictions that may affect operation of solar installations in the other's jurisdiction.	building permit.			FITS Minor VIA, July 2018).

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monite	="	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvar/Whitigation Weasures	Schedule	Responsibility	Project	References to Mitigation Measures)
3. Would the project cast shadow that substantially impairs the beneficial use of any public or quasipublic park, lawn, garden, or open space?	Mitigation 4.11-6: New construction adjacent to a public park or open space shall demonstrate through design review that development shall not substantially impair enjoyment of the public utilizing the space. Through design review, the City shall ensure that new building or landscaping shall not shade existing or proposed parks or open spaces in a manner that would make these public spaces substantially less useful or enjoyable to the public. The City may require specific building placement, tiered roofs, or other means of reducing shadow effects on public opens spaces. It is not the intent of this measure to completely eliminate shade in these areas, but to reduce shade to the maximum extent feasible.	Prior to the issuance of a building permit	City/Port	N/A	CMS located at intersection of 7th Street and Middle Harbor Road, adjacent to Middle Harbor Shoreline Park. Visual analysis indicates existing natural visual buffers (uniform row of trees on southwest side of intersection) and adequate distance from park in order to avoid substantial shadows on public or open spaces not. (FITS Minor VIA, July 2018).
Air Quality					
1. Would the project conflict with or obstruct implementation of the applicable air quality plan? 1. Would the project conflict with or obstruct implementation of the applicable air quality plan?	 SCA AIR-2: Construction-Related Air Pollution Controls (Dust and Equipment Emissions): During construction, the project applicant shall require the construction contractor to implement all of the following applicable measures recommended by the Bay Area Air Quality Management District (BAAQMD): a) Water all exposed surfaces of active construction areas at least twice daily (using reclaimed water if possible). Watering should be sufficient to prevent airborne dust from leaving the site. Increased watering frequency may be necessary whenever wind speeds exceed 15 miles per hour. Reclaimed water should be used whenever possible. b) Cover all trucks hauling soil, sand, and other loose materials or require all trucks to maintain at least two feet of freeboard (i.e., the minimum required space between the top of the load and the top of the trailer). c) All visible mud or dirt track-out onto adjacent public roads shall be removed using wet power vacuum street sweepers at least once per day. The use of dry power sweeping is prohibited. d) Pave all roadways, driveways, sidewalks, etc. as soon as feasible. In addition, building pads should be laid as soon as possible after grading unless seeding or soil binders are used. e) Enclose, cover, water twice daily or apply (non-toxic) soil stabilizers to exposed stockpiles (dirt, sand, etc.). f) Limit vehicle speeds on unpaved roads to 15 miles per hour. g) Idling times on all diesel-fueled commercial vehicles over 10,000 lbs. shall be minimized either by shutting equipment off when not is use or reducing the maximum idling time to five minutes (as required by Title 13, Section) 	Ongoing throughout demolition, grading, and/or construction	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. 7SGSW and 7SGSE projects included in Regional RTP, regional TIP and Federal-Statewide FSTIP. FITS project fully-exempt from conformity (40 CFR 93.126). Applies to all projects as an SCA CEQA mitigation. (7SGSE AQ Memo, June 2018; 7SGSW AQR, October 2018).

Environmental Impact		Standard Conditions of Annuaval/Mitiration Magazines	Mitigation Imp Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)	
		2485, of the California Code of Regulations. Clear signage to this effect shall be provided for construction workers at all access points.				
	h)	Idling times on all diesel-fueled off-road vehicles over 25 horsepower shall be shall be minimized either by shutting equipment off when not is use or reducing the maximum idling time to five minutes and fleet operators must develop a written idling policy (as required by Title 13, Section 2449 of the California Code of Regulations.)				
	i)	All construction equipment shall be maintained and properly tuned in accordance with the manufacturer's specifications. All equipment shall be checked by a certified mechanic and determined to be running in proper condition prior to operation.				
	j)	Post a publicly visible sign that includes the contractor's name and telephone number to contact regarding dust complaints. When contacted, the contractor shall respond and take corrective action within 48 hours. The telephone numbers of contacts at the City and the BAAQMD shall also be visible. This information may be posted on other required on-site signage.				
	k)	All exposed surfaces shall be watered at a frequency adequate to maintain minimum soil moisture of 12 percent. Moisture content can be verified by lab samples or moisture probe.				
	1)	All excavation, grading, and demolition activities shall be suspended when average wind speeds exceed 20 mph.				
	m)	Install sandbags or other erosion control measures to prevent silt runoff to public roadways.				
	n)	Hydroseed or apply (non-toxic) soil stabilizers to inactive construction areas (previously graded areas inactive for one month or more).				
	o)	Designate a person or persons to monitor the dust control program and to order increased watering, as necessary, to prevent transport of dust offsite. Their duties shall include holidays and weekend periods when work may not be in progress.				
	p)	Install appropriate wind breaks (e.g., trees, fences) on the windward side(s) of actively disturbed areas of the construction site to minimize wind blown dust. Wind breaks must have a maximum 50 percent air porosity.				
	q)	Vegetative ground cover (e.g., fast-germinating native grass seed) shall be planted in disturbed areas as soon as possible and watered appropriately until vegetation is established.				
	r)	The simultaneous occurrence of excavation, grading, and ground-disturbing construction activities on the same area at any one time shall be limited. Activities shall be phased to reduce the amount of disturbed surfaces at any one time.				

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvar/Mugation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	 s) All trucks and equipment, including tires, shall be washed off prior to leaving the site. t) Site accesses to a distance of 100 feet from the paved road shall be treated with a 6 to 12 inch compacted layer of wood chips, mulch, or gravel. u) All equipment to be used on the construction site and subject to the requirements of Title 13, Section 2449 of the California Code of Regulations ("California Air Resources Board Off-Road Diesel Regulations") must meet Emissions and Performance Requirements one year in advance of any fleet deadlines. The project applicant shall provide written documentation that the fleet requirements have been met. v) Use low VOC (i.e., ROG) coatings beyond the local requirements (i.e., BAAQMD Regulation 8, Rule 3: Architectural Coatings). 				
	Mitigation 4.4-3a: The Port shall develop and implement a criteria pollutant reduction program aimed at reducing or off-setting Port-related emissions in West Oakland from its maritime and rail operations to less than significant levels, consistent with applicable federal, state and local air quality standards. The program shall be sufficiently funded to strive to reduce emissions from redevelopment related contributors to local West Oakland air quality, and shall continually reexamine potential reductions toward achieving less than significant impacts as new technologies emerge. The adopted program shall define measurable reductions within specific time periods. This program shall be periodically reviewed and updated every one to three years, corresponding to regular updates of the CAP. The review and update shall include, and not be limited to, an assessment of any potential new strategies, a reassessment of funding requirements, technical feasibility, and cost benefit assumptions. Periodic updates shall be submitted to the City/Port Liaison Committee or its equivalent.	Prior to starting operations	Port	N/A	This measure does not apply to any of the projects. It addresses operation of ships and trains, which is out of the scope of the construction of the GoPort projects. This is not the responsibility of the GoPort engineers or contractors. (7SGSE AQ Memo, June 2018; 7SGSW AQR, October 2018).
	The pollutant reduction program shall give priority to emission reduction strategies that address PM ₁₀ emissions, but shall also provide for reductions in NO _x and ROG emissions. The emission reduction program shall include a list of potential emission reduction strategies. Strategies that shall be included in the program and implemented over the buildout period include: • The Port shall expand its existing cargo handling equipment re-powering and retrofitting program (part of the Berths 55-58 Project air quality mitigation program) to include marine and rail terminal yard equipment added or relocated as part of redevelopment build-out. • The Port shall extend its grant program (part of the Berths 55-58 Project				

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Imp Monite	=	GoPort	Notes (2018 GoPort Technical Studies References to Mitigation Measures)
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	
	operators at New Berth 21 and other Port facilities to implement emission reduction control measures or to replace tugboat engines to low NOx technology.				
	• The Port shall require rail terminal operators to use switch engines at the New Intermodal Facility that comply with federal air emission regulations for diesel operated locomotives as set forth in federal air regulations. In addition, the rail terminal operator and the Port are to exchange information with the goal of investigating options to accelerate compliance with Tier 0, 1 and 2 requirements of the federal regulations.				
	• The Port shall not preclude in its design of the New Intermodal Facility the installation of an alternative fueling station and shall to the extent feasible accommodate such a fueling station.				
	• The Port shall encourage ships to implement source control technologies when in the port area (such as reduced hoteling).				
	Other strategies to be included in the Port criteria pollutant reduction program when technically and economically feasible, include:				
	• Inclusion of an alternative fueling facility at the New Intermodal Facility.				
	Mitigation 4.4-3b (West Gateway Rail and Maritime Emissions Reduction Program): The ground lessee of the West Gateway and the Railroad Right of Way ("WG Ground Lessee") shall develop, for City review and approval, a criteria pollutant reduction program aimed at reducing or off-setting emissions from its rail-related and maritime-related operations, to the extent feasible, to less than significant levels, consistent with applicable federal, state and local air quality standards. The WG Ground Lessee shall implement the approved program and shall periodically review and update the program every one to three years, concurrently with the update of the Bay Area Clean Air Plan.	Prior to starting operations	City	N/A	7SGSW and 7SGSE projects included in Regional RTP, regional TIP and Federal-Statewide FSTIP. FITS project fully-exempt from conformity (40 CFR 93.126). Mitigation applies to rail and ships.
	The review and update shall include, and not be limited to, assessment of: potential new reduction strategies based on then-available technologies; funding requirements; technical feasibility; economic feasibility and cost benefit analysis. The updates shall be submitted to the City for its review and approval. The WG Ground Lessee shall implement the City-approved, updated program.				(7SGSE AQ Memo, June 2018; 7SGSW AQR, October 2018).
	The program shall give priority to emission reduction strategies that address PM ₁₀ emissions, but shall also provide for reductions in NO _X and ROG emissions. The emission reduction program shall include a list of potential emission reduction strategies and shall define measurable reduction goals within specific time periods. Strategies that shall be included in the program may include without limitation:				

Environmental Immed	Standard Conditions of Annuaral/Mitigation Magazines	Mitigation Im Monite	=	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	• Requiring rail terminal operators to use switch engines that comply with federal air emission regulations for diesel operated locomotives as set forth in federal air regulations. In addition, the rail terminal operator and the WG Ground Lessee to exchange information with the goal of investigating options to accelerate compliance with Tier 0, 1 and 2 requirements of the federal regulations.				
	• Encourage ships to implement source control technologies when in the West Gateway area (such as reduced hoteling).				
	\bullet Working with tugboat operators to implement emission reduction control measures or to replace tugboat engines to low NO_{X} technology.				
	 Mitigation 4.4-4: The City and the Port shall jointly create, maintain and fund on a fair share basis, a truck diesel emission reduction program. The program shall be sufficiently funded to strive to reduce redevelopment related contributions to local West Oakland diesel emissions to less than significant levels, consistent with applicable federal, state and local air quality standards, and shall continually reexamine potential reductions toward achieving less than significant impacts as new technologies emerge. The adopted program shall define measurable reduction within specific time periods. This program shall be periodically reviewed and updated every one to three years, corresponding to regular updates of the CAP. The review and update shall include, and not be limited to, an assessment of any potential new strategies, a reassessment of funding requirements, technical feasibility, and cost benefit assumptions. Periodic updates shall be submitted to the City/Port Liaison Committee or its equivalent. The diesel emissions reduction program shall include a list of potential emission reduction strategies that shall include on-site Port improvements and/or practices; loan, grant or incentive-based programs; and on-going studies. Strategies that shall be included in the diesel emissions reduction program and implemented over the build-out period include the following: On-site Port improvements. Configure truck parking in the Port to minimize traffic interference and reduce idling times. Allow easy access to a truck parking facility at the Port 24-hours a day. Synchronize traffic lights in the Port area to reduce congestion (requires coordination with the City). 	Prior to operations	City and Port	N/A	7SGSW and 7SGSE Projects included in Regional RTP, regional TIP and Federal-Statewide FSTIP. FITS project fully-exempt from conformity (40 CFR 93.126). Mitigation is for overall City/Port program, irrespective of GoPort projects. (7SGSE AQ Memo, June 2018; 7SGSW AQR, October 2018).

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental impact	Standard Conditions of Approva/Midgadon Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	 2. City/Port loan or grant/incentive programs for local businesses or entities. Provide incentives for re-powering, retrofitting, electrifying, or switching to alternative fuels to local businesses, franchises or truck fleets operating in West Oakland. Such businesses may include, for example, locally owned and operated trucking operations, refuse and recycling collection vehicles, school buses, Port and/or City fleet vehicles, and US Mail trucks. 				
	Other strategies to be included in the diesel emissions reduction program to be examined and incorporate when technically and economically feasible, include the following:				
	 On-site Port improvements. Allow trucks using alternative fuels to the head of queues or have separate gate entrances. 				
	2. On-going studies.Explore methods to minimize truck idling times at the Port.				
	• Explore and encourage the use of alternative fuels for Port marine, rail and truck operations.				
	• Propose and fund a random roadside heavy duty diesel vehicle (HDDV) emissions testing program and an HDDV repair subsidy program.				
	 3. City/Port loan or grant/incentive programs for local businesses or entities. Provide subsidies, training programs and/or voucher programs for local West Oakland businesses to conduct timing retard, compressions changes and other adjustments to diesel engines to reduce emissions. 				
	• Install oxidative catalyst and particulate traps on diesel engines with low NOx, alternatively fueled or electrified engines.				
	Mitigation Measure 4.4-5: Major developers ¹ shall fund on a fair share basis BAAQMD –recommended feasible Transportation Control Measures (TCMs) for reducing vehicle emissions from commercial, institutional, and industrial operations, as well as all CAP TCMs the BAAQMD has identified as appropriate for local implementation.	Prior to operations	City and Port and individual projects	N/A	7SGSW and 7SGSE projects included in Regional RTP, regional TIP and Federal-Statewide FSTIP. FITS project fully-exempt from conformity (40 CFR 93.126).
	Each major developer of a subsequent redevelopment activity shall fund its fair share toward some or all of the following TCMs:				(7SGSE AQ Memo, June 2018; 7SGSW AQR, October 2018).

7SGSW and 7SGSE

7SGSW and FITS

7SGSE and FITS

FITS

7SGSW

7SGSE

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Imp Monite	•	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvat/witigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	BAAQMD-Recommended Transportation Control Measure, Modified for this Action				
	Control Measure Measure				
	Construct transit facilities such as bus turnouts/bus bulbs, benches, shelters, etc. Improve transit bus service to the area.				
	Design and locate buildings to facilitate transit access, e.g., locate building entrances near transit stops, eliminate building setbacks, etc.				
	Provide and make public transit convenient for 16th and Wood sub-district residents and tenants. (<i>Note: Not applicable to the 2012 OARB Project</i>)				
	Encourage OARB sub-district tenants to use car pools, vanpools, and public transit by providing incentives.				
	5 Provide a shuttle to and from the West Oakland BART station				
	Provide on-site shops and services for employees, such as cafeteria, bank, dry cleaners, convenience market, etc.				
	Provide on-site child care, or contribute to off-site child care within walking distance.				
	Establish mid-day shuttle service from worksite to food service establishments/commercial areas.				
	9 Provide preferential parking for carpool and vanpool vehicles				
	10 Implement parking fees for single occupancy vehicle commuters.				
	Provide secure, weather-protected bicycle parking for employees.				
	Provide safe, direct access for bicyclists to adjacent bicycle routes.				
	Provide showers and lockers for employees bicycling or walking to work.				
	Provide direct, safe, attractive pedestrian access from project to transit stops and adjacent development.				
	Provide neighborhood-serving shops and services within or adjacent to the 16th and Wood sub-district. (Note: Not applicable to the 2012 OARB Project)				

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE

7SGSW and FITS

7SGSE and FITS

FITS

7SGSW

7SGSE

Environmental Impact	=		Mitigation Im Monite	=	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Stand	Standard Conditions of Approvar/Wingation Measures		Responsibility	Project	References to Mitigation Measures)
	"Mitigation Me	QMD 1996, as amended through 1999. Based on Table 15: easures for Reducing Motor Vehicle Emissions from astitutional, and Industrial Projects."				
	its fair share of t	loper of a subsequent redevelopment activity shall also fund he following CAP TCMs, which the BAAQMD has identified r local implementation, with redevelopment-specific				
	CAP TCMs	Description				
	Support Voluntary Employer- Based Trip Reduction Programs	The City and Port will explore ways to promote transit use and support employer-based trip reduction programs through development incentives such as density bonuses, reduced parking requirements, incentives for permanent bicycle facilities, etc. The City will encourage development of transit transfer stations near employment concentrations in the Gateway development area and 16th/Wood sub-district.				
	9. Improve Bicycle Access and Facilities	Redevelopment includes extensive multi-use trails serving as both "spine" thoroughfares and "spurs" connecting main trails to the Oakland waterfront. The City and Port will encourage employers and developers to provide permanent bicycle facilities.				
	12. Improve Arterial Traffic Manageme nt	Maritime Street and other roadways in the project area will include facilities to encourage bicycling and walking. Roadways and intersections will be designed to operate at City-standard LOS, to facilitate traffic flow and avoid unnecessary queuing.				
	15. Local Clean Air plans, Policies and Programs	Redevelopment as presented in Chapter 2.0 Project Description and Chapters 3.3 Air Quality and 3.16 Transportation and Traffic (in the 2012 OARB Project Initial Study/Addendum), incorporate land uses such as a rail terminal in conjunction with logistics uses, and				

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	_	plementation/ oring:	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvan/Mugation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	measures intended to reduce the number and length of truck trips and single-occupant automobile trips.				
	17. Conduct Demonstration Projects The City will encourage through development incentives demonstration projects for fleet electrification or alternative fueling. In addition, the Port will not preclude alternative fueling in its design of rail facilities.				
	19. Pedestrian OARB and Maritime sub-districts will include multi-use trails to encourage safe pedestrian travel.				
	20. Promote Traffic Calming Measures Redevelopment will include traffic calming measures to the extent appropriate, consistent with the General Plan and sound traffic management of the project area.				
	Source: BAAQMD CEQA Guidelines, revised 1999 Table 5.				
	These TCMs shall be coordinated with transportation demand management (TDM) measures implemented under SCA TRANS-1.				
	SCA TRANS-1: Parking and Transportation Demand Management, see Traffic and Transportation section below.			N/A	7SGSW and 7SGSE projects included in Regional RTP, regional TIP and Federal-Statewide FSTIP. FITS project fully-exempt from conformity (40 CFR 93.126).
					(7SGSE AQ Memo, June 2018; 7SGSW AQR, October 2018).
Would the project violate any air quality	See above for SCA AIR-2 and 2002 EIR Mitigation Measures 4.4-3a, 4.4-3l), 4.4-4, 4.4-5	<u> </u>		
violate any air quality standard or contribute substantially to an existing or projected air quality violation?	SCA AIR-1: Construction Management Plan: The project applicant shall submit to the Planning and Zoning Division and the Building Services Division for review and approval a construction management plan that identifies the conditions of approval and mitigation measures to construction impacts of the		City/Port	7SGSW 7SGSE FITS	Applies to Contractor. Mitigation applies as an SCA CEQA mitigation. One CMP should apply for all FITS Project

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE 7SGSW and FITS 7SGSE and FITS 7SGSW 7SGSE N/A

E	Standard Conditions of Approval/Mitigation Measures	Mitigation Imp Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	project and explains how the project applicant will comply with these construction-related conditions of approval and mitigation measures.				contracts, with separate CMP for the 7SGSW and 7SGSE Projects. Regional consultation determined that the 7SGSW and 7SGSE Project was not a Project of Air Quality Concern (POAQC). Analysis determined that it was
					unlikely the 7SGSW or 7SGSE Projects would interfere with State plans to attain and maintain
					NAAQS. FITS project fully- exempt from conformity (40 CFR 93.126).
					(7SGSE AQ Memo, June 2018; 7SGSW AQR, October 2018).
	Mitigation 4.4-6: Title 24 of the International Building Code (IBC) requires that new construction include energy-conserving fixtures and designs. Additionally, the City and Port shall implement sustainable development policies and strategies related to new development design and construction.	Prior to issuance of a demolition, grading, or building permit	City/Port	N/A	Measure does not apply to proposed projects. FITS TMC is rehabilitation-only.
	Implementation of IBC requirements would reduce the need for space and water heating that would emit pollutants.	81			
	 City and Port policies and strategies shall be conditioned for all new development within the redevelopment project area. Specific examples may include, and are not limited to the following: Wood fire heating shall be prohibited in new live/work development. Where siting allows and where feasible, buildings shall be oriented to take advantage of passive and active climate control designs. To the maximum extent feasible, central water heating systems shall be installed. 				
3. Would the project	See above for SCA AIR-2 and 2002 EIR Mitigation Measures 4.4-3a, 4.4-3b,	4.4-4, 4.4-5 and 4.4	1-6		
result in a cumulatively considerable net increase of any criteria air pollutant for which the project region is non-attainment under an applicable federal or state ambient air	Mitigation Measure 5.4-1: The City and the Port shall encourage, lobby, and potentially participate in emission reduction demonstration projects that promote technological advances in improving air quality.	Pre-operations; Operations	City and Port	N/A	7SGSW Project will increase criteria pollutants for which the San Francisco Bay Area falls under state or federal nonattainment, but will not exceed
	Such encouragement, lobbying, and participation may include the following: • Retrofitting locomotive engines to meet current federal standards.				per year de minimis levels or minimum thresholds for conformity.

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monite	=	GoPort	Notes (2018 GoPort Technical Studies
Environmental impact	Standard Conditions of Approvar/Wildgation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
quality standard (including releasing emissions which exceed quantitative thresholds for ozone precursors)?	 Using reduced sulfur fuels in ships while the ships are in the San Francisco Bay. Treating NO_x with selective catalytic reductions. Implementing random roadside emissions tests and develop a system of fines for trucks not in compliance with emission regulations. Establishing emissions-based berthing fees. Buying relatively old, highly polluting cars to take them off the road. 				7SGSE Project will increase criteria pollutants for which the San Francisco Bay Area falls under state or federal nonattainment, but will not exceed per year de minimis levels or minimum thresholds for conformity.
	Although these programs may assist in advancing emission reduction technologies or implementing emission reduction methods, the incremental				FITS project fully-exempt from conformity (40 CFR 93.126).
	contribution of the redevelopment program would remain cumulatively considerable, and the cumulative impact on air quality remains significant and unavoidable				(7SGSE AQ Memo, June 2018; 7SGSW AQR, October 2018).
4. Would the project result in a	See above SCA AIR-1, SCA AIR-2 and 2002 EIR Mitigation Measures 4.4-3.	a, 4.4-3b, 4.4-4, 4.4	-5 and 4.4-6		
cumulatively considerable net increase of any criteria air pollutant for which the project region is non-attainment under an applicable federal or state ambient air quality standard (including releasing emissions which exceed quantitative thresholds for ozone precursors)?	 SCA AIR-3: Exposure to Air Pollution (Toxic Air Contaminants: Particulate Matter): A. Indoor Air Quality: In accordance with the recommendations of the California Air Resources Board (ARB) and the Bay Area Air Quality Management District, appropriate measures shall be incorporated into the project design in order to reduce the potential health risk due to exposure to diesel particulate matter to achieve an acceptable interior air quality level for sensitive receptors. The appropriate measures shall include one of the following methods: 1) The project applicant shall retain a qualified air quality consultant to prepare a health risk assessment (HRA) in accordance with the ARB and the Office of Environmental Health and Hazard Assessment requirements to determine the exposure of project residents/occupants/users to air polluters prior to issuance of a demolition, grading, or building permit. The HRA shall be submitted to the Planning and Zoning Division for review and approval. The applicant shall implement the approved HRA recommendations, if any. If the HRA concludes that the air quality risks from nearby sources are at or below acceptable levels, then additional measures are not required. 2) The applicant shall implement all of the following features that have been found to reduce the air quality risk to sensitive receptors and shall be included in the project construction plans. These features shall be submitted to the Planning and Zoning Division and the 	Prior to issuance of a demolition, grading, or building permit	City/Port	N/A	Transisted and the state of the san Francisco Bay Area falls under state or federal nonattainment, but will not exceed per year de minimis levels or minimum thresholds for conformity. Transisted Bay Area falls under state or federal nonattainment, but will not exceed per year de minimis levels or minimum thresholds for conformity. Transisted Bay Area falls under state or federal nonattainment, but will not exceed per year de minimis levels or minimum thresholds for conformity. FITS project fully-exempt from conformity (40 CFR 93.126). Transisted Bay Area falls under state or federal nonattainment, but will not exceed per year de minimis levels or minimum thresholds for conformity.

Environmental Impact	Standard Conditions of Approval/Mitigation Measures		Mitigation Implementation/ Monitoring:		Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvar/Wingation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	Building Services Division for review and approval prior to the issuance of a demolition, grading, or building permit and shall be maintained on an ongoing basis during operation of the project.				
	 Redesign the site layout to locate sensitive receptors as far as possible from any freeways, major roadways, or other sources of air pollution (e.g., loading docks, parking lots). 				
	 Do not locate sensitive receptors near distribution center's entry and exit points. 				
	c) Incorporate tiered plantings of trees (redwood, deodar cedar, live oak, and/or oleander) to the maximum extent feasible between the sources of pollution and the sensitive receptors.				
	d) Install, operate and maintain in good working order a central heating and ventilation (HV) system or other air take system in the building, or in each individual residential unit, that meets or exceeds an efficiency standard of MERV 13. The HV system shall include the following features: Installation of a high efficiency filter and/or carbon filter to filter particulates and other chemical matter from entering the building. Either HEPA filters or ASHRAE 85% supply filters shall be used.				
	 Retain a qualified HV consultant or HERS rater during the design phase of the project to locate the HV system based on exposure modeling from the pollutant sources. 				
	f) Install indoor air quality monitoring units in buildings.				
	g) Project applicant shall maintain, repair and/or replace HV system on an ongoing and as needed basis or shall prepare an operation and maintenance manual for the HV system and the filter. The manual shall include the operating instructions and the maintenance and replacement schedule. This manual shall be included in the CC&Rs for residential projects and distributed to the building maintenance staff. In addition, the applicant shall prepare a separate homeowners manual. The manual shall contain the operating instructions and the maintenance and replacement schedule for the HV system and the filters.				
	B. Outdoor Air Quality: To the maximum extent practicable, individual and common exterior open space, including playgrounds, patios, and decks, shall either be shielded from the source of air pollution by buildings or otherwise buffered to further reduce air pollution for project occupants.				

7SGSW, 7SGSE, FITS

7SGSW and 7SGSE

7SGSW and FITS

7SGSE and FITS

7SGSW

7SGSE

7SGSE

7SGSW

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monite Schedule		GoPort Project	Notes (2018 GoPort Technical Studies References to Mitigation Measures)
Biological Resources					
1. Would the project have a substantial adverse effect, either directly or through habitat modifications, on any species identified as a candidate, sensitive, or special-status species in local or regional plans, policies, or regulations, or by the California Department of Fish and Game or U.S. Fish and Wildlife Service?	SCA BIO-1: Tree Removal During Breeding Season: To the extent feasible, removal of any tree and/or other vegetation suitable for nesting of raptors shall not occur during the breeding season of March 15 through August 15. If tree removal must occur during the breeding season, all sites shall be surveyed by a qualified biologist to verify the presence or absence of nesting raptors or other birds. Pre-removal surveys shall be conducted within 15 days prior to start of work from March 15 through May 31, and within 30 days prior to the start of work from June 1 through August 15. The pre-removal surveys shall be submitted to the Planning and Zoning Division and the Tree Services Division of the Public Works Agency. If the survey indicates the potential presences of nesting raptors or other birds, the biologist shall determine an appropriately sized buffer around the nest in which no work will be allowed until the young have successfully fledged. The size of the nest buffer will be determined by the biologist in consultation with the CDFG, and will be based to a large extent on the nesting species and its sensitivity to disturbance. In general, buffer sizes of 200 feet for raptors and 50 feet for other birds should suffice to prevent disturbance to birds nesting in the urban environment, but these buffers may be increased or decreased, as appropriate, depending on the bird species and the level of disturbance anticipated near the nest.	Prior to issuance of a tree removal permit	City/Port	7SGSW 7SGSE	Applies to Contractor. The 7SGSW BSA contains 168 ornamental street trees, many of which may provide potential nesting habitat for birds protected under the MBTA. 7SGSW Project will adhere to SCA Bio 1. The 7SGSE BSA contains 31 ornamental street trees, many of which may provide potential nesting habitat for birds protected under the MBTA. 7SGSE Project will adhere to SCA Bio 1. The FITS BSA contains 166 street trees, many of which may provide potential nesting habitat for birds protected under the MBTA. (7SGW NES, May 2018; 7SGSE NES May 2018; FITS Bio Memo, June 2018).

		Mitigation Im Monit		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	SCA BIO-5 Regulatory Permits and Authorizations: Prior to construction in or near the water, the project applicant shall obtain all necessary regulatory permits and authorizations, including without limitation, from the U.S. Army Corps of Engineers (Corps), Regional Water Quality Control Board (RWQCB), San Francisco Bay Conservation and Development Commission (BCDC) and the City of Oakland, and shall comply with all conditions issued by applicable agencies. Required permit approvals and certifications may include, but not be limited to the following:	Prior to issuance of a demolition, grading, or building permit within vicinity of the shoreline	City/Port	N/A	The following permits are not applicable to the GoPort projects. (7SGW NES, May 2018; 7SGSE NES, May 2018; FITS Bio Memo, June 2018).
	a) U.S. Army Corps of Engineers (Corps): Section 404. Permit approval from the Corps shall be obtained for the placement of dredge or fill material in Waters of the U.S., if any, within the interior of the project site, pursuant to Section 404 of the federal Clean Water Act.				
	b) Regional Walter Quality Control Board (RWQCB): Section 401 Water Quality Certification. Certification that the project will not violate state water quality standards is required before the Corps can issue a 404 permit, above.				
	c) San Francisco Bay Conservation and Development Commission (BCDC) approvals.				
	Mitigation Measure 4.12-5: A qualified observer shall be present on site during all in-water construction activities near potential herring spawning areas between December 1 and March 1.	During construction	City/Port	N/A	No in-water construction activities required for the GoPort projects.
	This measure shall be enforced via contract specifications. The observer shall have the authority to redirect, but not to stop work.				
	Mitigation Measure 4.12-6: If spawning is observed, in-water construction activities shall be redirected for 200 meters around the spawning area for two weeks.	During construction	City/Port	N/A	No in-water construction activities required for the GoPort projects.
	Work may resume in the spawning area after two weeks, providing additional spawning does not occur. This measure shall be enforced via contract specifications.				
	Mitigation Measure 4.12-10: The Port shall continue to enforce its tariff requirements regarding ballast water and if the State law sunsets, shall implement the remainder of its ballast water ordinance, as it may be amended from time to time.	During construction	Port	N/A	Ballast water activities not required for the GoPort projects.
	Item No. 02215 of the Port's tariff (its operating rules and regulations) defines the Port's Ballast Water Management Program. Among other things, the Port's program compiles information regarding the ballasting behavior of carriers				

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monite	-	GoPort	Notes (2018 GoPort Technical Studies
Environmental impact		Schedule	Responsibility	Project	References to Mitigation Measures)
	calling at the Port of Oakland. This information is expected to be valuable in crafting durable solutions to the problems ballast water-borne invasive species pose to the ecology of the Bay, and to invasive species issues elsewhere. This mitigation measure would continue the Port's program through the build-out year of this project, or 2020, or until required by regulatory permit conditions, whichever is later. Should portions of the Port's program be redundant to federal, state, or regional programs, or be pre-empted by such programs, the Port will continue to operate those non-pre-empted portions of its program that provide information not obtained through other programs.				
	Modified Mitigation Measure 4.12-11: The Port, and developer and subtenants at Berths 7 and 8 (Wharves 6½ and 7), shall continue to develop and implement a carrier ballast water education program.	Operations	City/Port	N/A	Ballast water activities not required for the GoPort projects.
	Either by itself or by participating in programs by others, e.g., Sea Grant, the Port and developer and sub-tenants at Berths 7 and 8 (Wharves 6½ and 7), shall create a program to educate ocean carriers regarding the potential harm of ballasting activities. The program shall at a minimum, include the following elements: • Educate carriers to all applicable regulations and guidelines. • Inform carriers of the benefits of ships constructed with internal ballast water transfer systems. These systems allow ballast water to be shifted internally from tank to tank, minimizing or eliminating the need for discharge of ballast water when ships are at berth • Encourage carriers to purchase internally-ballasting vessels when they place orders for new ships. • Educate carriers regarding potential benefits of reducing ballast water discharges, even if ballast water has already been exchanged in the open ocean.				
	Modified Mitigation Measure 4.12-12: The Port, and developer and subtenants at Berths 7 and 8 (Wharves 6½ and 7), shall support international and United States efforts to adopt uniform international or national standards to avoid introduction of exotic species through shipping activities. The Port, and developer and sub-tenants at Berths 7 and 8 (Wharves 6½ and 7)	Operations	City/Port	N/A	No proposed GoPort project activities at Berths 7 and 8.
	shall provide in-kind (personnel) support to assist international and U.S. entities to develop and adopt a uniform set of standards to reduce the risk of invasive species. In order to achieve optimal environmental success and to maintain a competitive market between ports, it is important that such standards be effective and uniformly applied.				

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE 7SGSW and FITS 7SGSE and FITS 7SGSW 7SGSE N/A

	Standard Conditions of America 1954 and the Manager	Mitigation Imp		GoPort	Notes (2018 GoPort Technical Studies References to Mitigation Measures)
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	
	Mitigation Measure 3.4-1a: The developer shall submit a Landscape Plan for City review and approval. The plan shall not include tall ornamental trees that could provide perches for raptors in the northern project site, in the vicinity of Gateway Park.	Prior to issuance of a building permit, associated with the Planned Unit Development (PUD) process	City/Port	7SGSW 7GSSE FITS	Applies to design phase only.
	Mitigation Measure 3.4-1b: The developer shall submit a Lighting Plan for City review and approval. The plan shall note that raptor deterrents shall be placed on light standards in the northern project site, in the vicinity of Gateway Park, or lighting fixtures or posts in the area shall have limited horizontal elements which could be used as perches.	Prior to issuance of a building permit, associated with the Planned Unit Development (PUD) process	City/Port	7SGSW 7GSSE FITS	Applies to design phase only.
2. Would the project have a substantial adverse effect on any riparian habitat or other sensitive natural community identified in local or regional plans, policies, regulations or by the California Department of Fish and Game or US Fish and Wildlife Service?	See above for Modified 2002 EIR Mitigation Measures 4.12-11 and 4.12-12				
3. Would the project have a substantial adverse effect on federally protected wetlands (as defined by Section 404 of the Clean Water Act) or state protected wetlands, through direct removal, filling, hydrological interruption, or other means?	See above for SCA BIO-5				

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monite	oring:	GoPort	Notes (2018 GoPort Technical Studies
		Schedule	Responsibility	Project	References to Mitigation Measures)
4. Would the project substantially interfere with the movement of any native resident or migratory fish or wildlife species or with established native resident or migratory wildlife corridors, or impede the use of native wildlife nursery sites?	See above for Mitigation Measures 4.12-5, 4.12-6, 4.12-11 and 4.12-12				
5. Would the project fundamentally conflict with the City of Oakland Tree Protection Ordinance (Oakland Municipal Code (OMC) Chapter 12.36) by removal of protected trees under certain circumstances?	SCA BIO-2: Tree Removal Permit: Prior to removal of any protected trees, per the Protected Tree Ordinance, located on the project site or in the public right-of-way adjacent to the project, the project applicant must secure a tree removal permit from the Tree Division of the Public Works Agency, and abide by the conditions of that permit.	Prior to issuance of a demolition, grading, or building permit.	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. The Port has land use jurisdiction within the majority of the GoPort Project limits and will issue tree removal permits pursuant to the SCAs identified in the OAB Project's SCA/MMRP within the Port area. The City of Oakland's tree ordinance requires the replacement of specific tree species removed within the City right-of-way. Although the City's Protected Tree Ordinance does not apply to the Port, and the Port is not required to obtain tree removal permits, the Port has committed to issuing tree removal permits pursuant to the Standard Conditions of Approval identified in the SCA/MMRP.
	<u>SCA BIO-3: Tree Replacement Plantings</u> : Replacement plantings shall be required for erosion control, groundwater replenishment, visual screening and wildlife habitat, and in order to prevent excessive loss of shade, in accordance with the following criteria:	Prior to issuance of a final inspection of the building permit.	City/Port	N/A	SCA Bio-3 determined not applicable for GoPort Projects. (7SGW NES, May 2018, 7SGSE NES, May 2018, FITS Bio Memo, June 2018).
	a) No tree replacement shall be required for the removal of nonnative species, for the removal of trees which is required for the benefit of remaining trees, or where insufficient planting area exists for a mature tree of the species being considered.				

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE 7SGSW and FITS 7SGSE and FITS

FITS

7SGSW

7SGSE

Environmental Impact		Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monite	=	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact		Standard Conditions of Approva/Mugation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	b)	Replacement tree species shall consist of Sequoia sempervirens (Coast Redwood), Quercus agrifolia (Coast Live Oak), Arbutus menziesii (Madrone), Aesculus californica (California Buckeye) or Umbellularia californica (California Bay Laurel) or other tree species acceptable to the Tree Services Division.				
	c)	Replacement trees shall be at least of twenty-four (24) inch box size, unless a smaller size is recommended by the arborist, except that three fifteen (15) gallon size trees may be substituted for each twenty-four (24) inch box size tree where appropriate.				
	d)	Minimum planting areas must be available on site as follows:i. For Sequoia sempervirens, three hundred fifteen square feet per tree;ii. For all other species listed in #2 above, seven hundred (700) square feet per tree.				
	e)	In the event that replacement trees are required but cannot be planted due to site constraints, an in lieu fee as determined by the master fee schedule of the city may be substituted for required replacement plantings, with all such revenues applied toward tree planting in city parks, streets and medians.				
	f)	Plantings shall be installed prior to the issuance of a final inspection of the building permit, subject to seasonal constraints, and shall be maintained by the project applicant until established. The Tree Reviewer of the Tree Division of the Public Works Agency may require a landscape plan showing the replacement planting and the method of irrigation. Any replacement planting which fails to become established within one year of planting shall be replanted at the project applicant's expense.				
	sha	A BIO-4: Tree Protection During Construction: Adequate protection ll be provided during the construction period for any trees which are to nain standing, including the following, plus any recommendations of an orist:	Prior to issuance of a demolition, grading, or building permit.	City/Port	7SGSE 7SGSW FITS	Applies to Contractor. Included in the 7SGSW and 7SGSE NES and FITS Biological Technical Memo.
	a)	Before the start of any clearing, excavation, construction or other work on the site, every protected tree deemed to be potentially endangered by said site work shall be securely fenced off at a distance from the base of the tree to be determined by the City Tree Reviewer. Such fences shall remain in place for duration of all such work. All trees to be removed shall be clearly marked. A scheme shall be established for the removal and disposal of logs, brush, earth and other debris which will avoid injury to any protected tree.				
	b)	Where proposed development or other site work is to encroach upon the protected perimeter of any protected tree, special measures shall be				

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit	="	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvar/wingation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	incorporated to allow the roots to breathe and obtain water and nutrients. Any excavation, cutting, filing, or compaction of the existing ground surface within the protected perimeter shall be minimized. No change in existing ground level shall occur within a distance to be determined by the City Tree Reviewer from the base of any protected tree at any time. No burning or use of equipment with an open flame shall occur near or within the protected perimeter of any protected tree.				
	c) No storage or dumping of oil, gas, chemicals, or other substances that may be harmful to trees shall occur within the distance to be determined by the Tree Reviewer from the base of any protected trees, or any other location on the site from which such substances might enter the protected perimeter. No heavy construction equipment or construction materials shall be operated or stored within a distance from the base of any protected trees to be determined by the tree reviewer. Wires, ropes, or other devices shall not be attached to any protected tree, except as needed for support of the tree. No sign, other than a tag showing the botanical classification, shall be attached to any protected tree.				
	d) Periodically during construction, the leaves of protected trees shall be thoroughly sprayed with water to prevent buildup of dust and other pollution that would inhibit leaf transpiration.				
	e) If any damage to a protected tree should occur during or as a result of work on the site, the project applicant shall immediately notify the Public Works Agency of such damage. If, in the professional opinion of the Tree Reviewer, such tree cannot be preserved in a healthy state, the Tree Reviewer shall require replacement of any tree removed with another tree or trees on the same site deemed adequate by the Tree Reviewer to compensate for the loss of the tree that is removed.				
	f) All debris created as a result of any tree removal work shall be removed by the project applicant from the property within two weeks of debris creation, and such debris shall be properly disposed of by the project applicant in accordance with all applicable laws, ordinances, and regulations.				
Cultural Resources			Ī		
1. Would the project cause a substantial adverse change in the significance of a historical resource as defined in CEQA Guidelines Section	Element (Property Relocation Rather than Demolition) The project applicant shall make a good faith effort to relocate the buildings considered contributors to the Historic District to a site acceptable to the Planning and Zoning Division and the Oakland Cultural Heritage Survey. Good faith efforts include at a minimum, the following:	Prior to issuance of a demolition permit	City/Port	N/A	GoPort projects elements not located within OARB Historic District.
					Caltrans and SHPO determined that historical resources within the APE of the 7SGSE Project are not eligible for listing in the NHRP. It

	Mitigation Implementation/ Monitoring:		GoPort	Notes
Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	(2018 GoPort Technical Studies References to Mitigation Measures)
a) Advertising the availability of the building by: (1) posting of large visible signs (such as banners, at a minimum of 3'x 6' size or larger) at the site; (2) placement of advertisements in Bay Area news media acceptable to the City; and (3) contacting neighborhood associations and for-profit and not-for-profit housing and preservation organizations;				has been determined that resources within the 7SGSW APE are not eligible for listing in the NHRP (pending SHPO concurrence). Caltrans determined a Finding of
 Maintaining a log of all the good faith efforts and submitting that along with photos of the subject building showing the large signs (banners) to the Planning and Zoning Division; 				No Historic Properties Affected for the FITS Project.
c) Maintaining the signs and advertising in place for a minimum of 90 days; and				(7SGSW HPSR, September 2018, 7SGSE HPSR, May 2018, FITS HPSR, August 2018).
d) Making the building available at no or nominal cost (the amount to be reviewed by the Oakland Cultural Heritage Survey) until removal is necessary for construction of a replacement project, but in no case for less than a period of 90 days after such advertisement.				
Mitigation Measure 4.6-2: The City, Port and OARB sub-district developers shall fund on a fair-share basis development of a commemoration site, including preparation of a Master Plan for such a site, at a public place located within the Gateway development area. The City shall ensure that the scale and scope of the commemoration site reflects the actual loss of historic resources.	Prior to approval of PUD.	City and Port	N/A	Caltrans and SHPO determined that historical resources within the APE of the 7SGSE Project are not eligible for listing in the NHRP. It has been determined that resources within the 7SGSW APE
accessible place located within the Gateway development area (potentially the Gateway Park at the Bay Bridge touchdown peninsula). The commemoration site should include relocated physical elements of the OARB Historic District, along with appropriate monument(s) to memorialize the contributions of				are not eligible for listing in the NHRP (pending SHPO concurrence). Caltrans determined a Finding of No Historic Properties Affected
• An appropriate location shall be set aside for development of a commemoration site. The commemoration site shall be at a publicly accessible place. It may be located within or adjacent to any historic district contributor buildings that are preserved on a permanent basis (see Mitigation Measure 4.6-16). If that is not feasible, another potential location is within or near to the Gateway Park.				for the FITS Project. (7SGSW HPSR, September 2018; 7SGSE HPSR, May 2018; FITS HPSR, August 2018).
• A design plan for the commemoration site shall be prepared, and shall include the design of monuments and the selection of appropriate relocated physical elements from the OARB, potentially including relocated structures or portions of structures to be included in the site. The City and the Port shall identify structures and/or portions of structures to be preserved or moved to the commemoration site prior to demolition.				
	 a) Advertising the availability of the building by: (1) posting of large visible signs (such as banners, at a minimum of 3'x 6' size or larger) at the site; (2) placement of advertisements in Bay Area news media acceptable to the City; and (3) contacting neighborhood associations and for-profit and not-for-profit housing and preservation organizations; b) Maintaining a log of all the good faith efforts and submitting that along with photos of the subject building showing the large signs (banners) to the Planning and Zoning Division; c) Maintaining the signs and advertising in place for a minimum of 90 days; and d) Making the building available at no or nominal cost (the amount to be reviewed by the Oakland Cultural Heritage Survey) until removal is necessary for construction of a replacement project, but in no case for less than a period of 90 days after such advertisement. Mitigation Measure 4.6-2: The City, Port and OARB sub-district developers shall fund on a fair-share basis development of a commemoration site, including preparation of a Master Plan for such a site, at a public place located within the Gateway development area. The City shall ensure that the scale and scope of the commemoration site reflects the actual loss of historic resources. Land shall be set aside for development of a commemoration site at a publicly accessible place located within the Gateway development area (potentially the Gateway Park at the Bay Bridge touchdown peninsula). The commemoration site should include relocated physical elements of the OARB Historic District, along with appropriate monument(s) to memorialize the contributions of civilians and the military in the Bay Area to all wars. An appropriate location shall be set aside for development of a commemoration site. The commemoration is te shall be at a publicly accessible place. It may be located within or adjacent to any historic district contributor buildings that are preserved on a permanent basis (see M	a) Advertising the availability of the building by: (1) posting of large visible signs (such as banners, at a minimum of 3'x o' size or larger) at the site; (2) placement of advertisements in Bay Area news media acceptable to the City; and (3) contacting neighborhood associations and for-profit and not-for-profit housing and preservation organizations; b) Maintaining a log of all the good faith efforts and submitting that along with photos of the subject building showing the large signs (banners) to the Planning and Zoning Division; c) Maintaining the signs and advertising in place for a minimum of 90 days; and d) Making the building available at no or nominal cost (the amount to be reviewed by the Oakland Cultural Heritage Survey) until removal is necessary for construction of a replacement project, but in no case for less than a period of 90 days after such advertisement. Mitigation Measure 4.6-2: The City, Port and OARB sub-district developers shall fund on a fair-share basis development of a commemoration site, including preparation of a Master Plan for such a site, at a public place located within the Gateway development area. The City shall ensure that the scale and scope of the commemoration site reflects the actual loss of historic resources. Land shall be set aside for development of a commemoration site at a publicly accessible place located physical elements of the OARB Historic District, along with appropriate monument(s) to memorialize the contributions of civilians and the military in the Bay Area to all wars. • An appropriate location shall be set aside for development of a commemoration site. The commemoration site shall be at a publicly accessible place. It may be located within or adjacent to any historic district contributor buildings that are preserved on a permanent basis (see Mitigation Measure 4.6-16). If that is not feasible, another potential location is within or near to the Gateway Park. • An design plan for the commemoration site shall be prepared, and shall include the design of	Advertising the availability of the building by; (1) posting of large visible signs (such as banners, at a minimum of 3'x 6' size or larger) at the site; (2) placement of advertisements in Bay Area news media acceptable to the City and (3) contacting neighborhood associations and for-profit and not-for-profit housing and preservation organizations; b) Maintaining a log of all the good faith efforts and submitting that along with photos of the subject building showing the large signs (banners) to the Planning and Zoning Division; c) Maintaining the signs and advertising in place for a minimum of 90 days; and d) Making the building available at no or nominal cost (the amount to be reviewed by the Oakland Cultural Heritage Survey) until removal is necessary for construction of a replacement project, but in no case for less than a period of 90 days after such advertisement. Mitigation Measure 4.6-2: The City, Port and OARB sub-district developers shall fund on a fair-share basis development of a commemoration site, call the district of the commemoration is an abster Plan for such a site, at a public place located within the Gateway development area. The City shall ensure that the scale and scope of the commemoration is tereflects the actual loss of historic resources. Land shall be set aside for development of a commemoration site and the military in the Bay Area to all wars. * An appropriate monument(s) to memorialize the contributions of civilians and the military in the Bay Area to all wars. * An appropriate location shall be set aside for development of a commemoration site. The commemoration is exhall be at a publicly accessible place. It may be located within to adjacent to any historic district contributor buildings that are preserved on a permanent basis (see Mitigation Measure 4.6-16). If that is not feasible, another potential location is within or near to the Gateway Park. A design plan for the commemoration site shall be prepared, and shall include the design of monuments and the selection of ap	Standard Conditions of Approval/Mitigation Measures Schedule Responsibility

Environmental Import	Standard Conditions of Annuaral Mitigation Magazines	Mitigation Im Monit	=	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	 public and interested historical and veterans groups, historic experts, and other public agencies. Implementation of the commemoration site master plan may be phased along with the timing of new development. The master plan shall include an endowment to be funded by the City and the Port, or their designee, for on-going maintenance and replacement and may also include curator costs associated with commemoration site and with trail signage, exhibits, and design elements as described below. The City and the Port shall develop an ongoing outreach program informing the public of the importance of the OARB to the community and the region, and of the existence of the commemorative site. Mitigation Measure 4.6-3: The City shall ensure the commemoration site is linked to the Gateway Park and the Bay Trail via a public access trail. Within the Gateway development area, this trail may be located along the shoreline. Beyond the Gateway, the trail would follow the new alignment of Maritime Street, connecting to 7th Street, which connects to the Port's Middle Harbor Shoreline Park and other existing and planned trail segments. The design and development of this on-site trail shall include a series of interpretive panels, exhibits and design elements that communicate the scope and historical significance of Base activities and their impact on the community throughout the life of the Base. 	Prior to approval of PUD.	City and Port	N/A	
	• A brochure shall be developed and made available describing the history of the Army Base that could be used as a self-guided tour, related to the interpretive panels and exhibits described above.				
	 Mitigation Measure 4.6-5: The City, Port, and OARB sub-district developers shall fund on a fair share basis collaboration with "military.com" or a similar military history web site. The parties shall fund development of an interactive web page to be provided to military.com or other web-based organization where former military personnel can be connected to the OARB documentation. A list of list of draftees/enlistees processed through the OARB during WWII and the Korean and Vietnam Wars may be an element of such a site. 	Prior to issuance of a building permit	City and Port	N/A	Caltrans and SHPO determined that historical resources within the APE of the 7SGSE Project are not eligible for listing in the NHRP It has been determined that resources within the 7SGSW APE are not eligible for listing in the NHRP (pending SHPO concurrence). Caltrans determined a Finding of No Historic Properties Affected for the FITS Project. (7SGSW HPSR, September 2018; 7SGSE HPSR, May 2018; FITS HPSR, August 2018).

FITS

7SGSW

7SGSE

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Imp Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental impact	Standard Conditions of Approvativitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	Mitigation Measure 4.6-7: If determined of significant historical educational value by the Oakland Landmarks Preservation Advisory Board and the Oakland Heritage Alliance, the City, Port, and OARB sub-district developers shall fund on a fair share basis distribution of copies of "A Job Well Done" documentary video published by the Army.	Prior to issuance of a building permit City and Port	City and Port	N/A	Caltrans and SHPO determined that historical resources within the APE of the 7SGSE Project are not eligible for listing in the NHRP It has been determined that
	The Army has produced a television broadcast–quality video documentary that describes the mission and historical significance of the OARB. This documentary is not widely distributed, and has not been viewed by the Oakland Landmarks Preservation Advisory Board or the Oakland Heritage Alliance. This				resources within the 7SGSW APE are not eligible for listing in the NHRP (pending SHPO concurrence).
	documentary is currently available to the public, but is not widely distributed. This mitigation measure will ensure that the documentary is widely distributed and made available to a larger audience interested in the history of the Base. It				Caltrans determined a Finding of No Historic Properties Affected for the FITS Project.
	will also offset the modification and/or destruction of many of the historic buildings on the base, preserve their images, and provide a description of their function and role to the interested public. Copies of the video shall be distributed to: the Oakland History Room, Oakland Public Library, Bancroft Library, University of California; the Port of Oakland Archives; local public schools and libraries; and local public broadcasting stations. Funding shall also be used to copy this video onto more permanent archive-stable medium such as a CD.			(7SGSW HPSR, September 2018; 7SGSE HPSR, May 2018; FITS HPSR, August 2018).	
	Mitigation Measure 4.6-9: The City, Port, and OARB sub-district developers shall fund on a fair share basis a program to salvage as whole timber posts, beams, trusses and siding of warehouses to be deconstructed. These materials shall be used on site if deconstruction is the only option. Reuse of a warehouse building or part of a warehouse building at its current location, or relocated to another Gateway location is preferable.	Prior to issuance of a building permit	City and Port	N/A	Caltrans and SHPO determined that historical resources within the APE of the 7SGSE Project are not eligible for listing in the NHRP It has been determined that resources within the 7SGSW APE
	To the extent feasible, these materials shall be used in whole, on site, in the construction of new buildings within the Gateway development area. Special consideration shall be given to the use of these materials at the commemoration site through the cite? Moster Planning offert				are not eligible for listing in the NHRP (pending SHPO concurrence).
	site through the site's Master Planning effort. If on-site reuse is found infeasible, opportunities shall be sought for reuse of these materials in other East Bay Area construction, or be sold into the recycled construction materials market. Landfill disposal of salvageable construction				Caltrans determined a Finding of No Historic Properties Affected for the FITS Project. (7SGSW HPSR, September 2018, 7SGSE
	material from contributing historic structures shall be prohibited by contract specification. Salvage and reuse requirements shall be enforced via contract specification.				HPSR, May 2018, FITS HPSR, August 2018).
	Salvage operations shall employ members of local job-training bridge programs (Youth Employment Program, Joint Apprenticeship Training Committee, Homeless Collaborative) or other similar organizations, if feasible, to provide construction-training opportunities to Oakland residents.				

Environmental Irreset		Mitigation Implementation/ Monitoring:		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	Salvage and reuse of the timber from these structures will help to reduce the impacts on the environment and save this ecologically and historically valuable material for reuse in the local community.				
	 Mitigation Measure 4.6-10: The City, Port, and OARB sub-district developers shall fund on a fair share basis production of a brochure describing history and architectural history of the OARB. The brochure shall be distributed to local libraries and schools, and be made available to the public at select pick-up and drop-off locations along the Bay Trail to be used for self-guided tours. This brochure shall build upon the previously completed historical documentation produced by the Port of Oakland, the Navy, and the Army for previous projects and on the original research completed for preparation of the Historical Resource Documentation Program and book. This brochure shall will document the history of the redevelopment area and provide references to where more detailed information about the Base may be found. 	Prior to issuance of a building permit	City and Port	N/A	Caltrans and SHPO determined that historical resources within the APE of the 7SGSE Project are not eligible for listing in the NHRP It has been determined that resources within the 7SGSW APE are not eligible for listing in the NHRP (pending SHPO concurrence). Caltrans determined a Finding of No Historic Properties Affected for the FITS Project. (7SGSW HPSR, September 2018, 7SGSE HPSR, May 2018, FITS HPSR, August 2018).
	Modified Mitigation Measure 4.6-14: No demolition or deconstruction of contributing structures to the OARB Historic District shall occur until a master plan and/or Lease Disposition and Development Agreement has been approved by the City, and demolition or deconstruction of a building is required to realize the master infrastructure development plan necessary for approved redevelopment activities, in conformity with applicable General Plan Historic Preservation Element and City of Oakland Planning requirements. ³	Approval of master plan and/or Lease Disposition and Development Agreement	City/Port	N/A	Caltrans and SHPO determined that historical resources within the APE of the 7SGSE Project are not eligible for listing in the NHRP It has been determined that resources within the 7SGSW APE are not eligible for listing in the NHRP (pending SHPO concurrence). Caltrans determined a Finding of No Historic Properties Affected for the FITS Project. (7SGSW HPSR, September 2018, 7SGSE HPSR, May 2018, FITS HPSR, August 2018).

³ The 2002 EIR mitigation measure 4.6-14 states that the Port shall not demolish or deconstruct structures until it has approved a final development plan for the relevant new facility or facilities. This requirement shall continue to apply to the Port in the absence of a Lease Disposition and Development Agreement.

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring:		GoPort	Notes (2018 GoPort Technical Studies
_		Schedule	Responsibility	Project	References to Mitigation Measures)
2. Would the project cause a substantial adverse change in the significance of an archaeological resource pursuant to CEQA Guidelines Section 15064.5?	 SCA CULT-1: Archaeological Resources: a) Pursuant to CEQA Guidelines section 15064.5 (f), "provisions for historical or unique archaeological resources accidentally discovered during construction" should be instituted. Therefore, in the event that any prehistoric or historic subsurface cultural resources are discovered during ground disturbing activities, all work within 50 feet of the resources shall be halted and the project applicant and/or lead agency shall consult with a qualified archaeologist or paleontologist to assess the significance of the find. If any find is determined to be significant, representatives of the project proponent and/or lead agency and the qualified archaeologist would meet to determine the appropriate avoidance measures or other appropriate measure, with the ultimate determination to be made by the City of Oakland. All significant cultural materials recovered shall be subject to scientific analysis, professional museum curation, and a report prepared by the qualified archaeologist according to current professional standards. b) In considering any suggested measure proposed by the consulting archaeological resources, the project applicant shall determine whether avoidance is necessary and feasible in light of factors such as the nature of the find, project design, costs, and other considerations. If avoidance is unnecessary or infeasible, other appropriate measures (e.g., data recovery) shall be instituted. Work may proceed on other parts of the project site while measure for historical resources or unique archaeological resources is carried out. c) Should an archaeological artifact or feature be discovered on-site during project construction, all activities within a 50-foot radius of the find would be halted until the findings can be fully investigated by a qualified archaeologist to evaluate the find and assess the significance of the find according to the CEQA definition of a historical or unique archaeological resource. If the deposit is determ	Ongoing throughout demolition, grading, and/or construction.	City/Port	7SGSW 7SGE FITS	Applies to Contractor. No known archaeological sites are within the 7SGSW or 7SGSE APE. No known archaeological sites are located within the FITS APE. Although one subsurface linear resource (sewer pipe) passes through the horizontal APE, it has been exempted under the Programmatic Agreement Property Type 1 (water supply and waste disposal systems). (7SGSW ASR, May 2018, 7SGSE ASR, September 2018, FITS ASR, August 2018)

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Imp Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental impact	Standard Conditions of Approva/Midgadon Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	 Require storage (curation) of recovered materials, such as artifacts and soil samples, and records generated by an archaeological study in a facility that allows access to the materials. 				
3. Would the project directly or indirectly destroy a unique paleontological resource or site or unique geologic feature?	SCA CULT-3: Paleontological Resources: In the event of an unanticipated discovery of a paleontological resource during construction, excavations within 50 feet of the find shall be temporarily halted or diverted until the discovery is examined by a qualified paleontologist (per Society of Vertebrate Paleontology standards [SVP 1995,1996]). The qualified paleontologist shall document the discovery as needed, evaluate the potential resource, and assess the significance of the find under the criteria set forth in Section 15064.5 of the CEQA Guidelines. The paleontologist shall notify the appropriate agencies to determine procedures that would be followed before construction is allowed to resume at the location of the find. If the City determines that avoidance is not feasible, the paleontologist shall prepare an excavation plan for mitigating the effect of the project on the qualities that make the resource important, and such plan shall be implemented. The plan shall be submitted to the City for review and approval.	Ongoing throughout demolition, grading, and/or construction.	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. The ground disturbance associated with the 7SGSE Project has the potential to encounter landforms that would have been suitable for prehistoric use and activities; however, the probability of encountering a deeply buried archaeological site in the APE below artificial fill and Bay Muds is probably low. For the 7SGSW Project, archaeological monitoring is recommended where construction plans call for excavation between 20 to 30 feet below the surface that may penetrate the fill and disturb underlying native sediments where stable landforms were once present. The locations and depths proposed for archaeological monitoring will be further refined during final design once specific locations and extents are identified for construction elements that extend below the fill. The majority of ground disturbance within the FITS APE is limited to a depth of 24-30 inches for installation of conduit. For the few project elements that have the potential to extend beyond the fill and disturbed deposits and into the Bay Muds and older native deposits, these locations are considered to have

1	Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring: Schedule Responsibili		GoPort Project	Notes (2018 GoPort Technical Studies References to Mitigation
4.	Would the project	SCA CULT-2: Human Remains: In the event that human skeletal remains are	Ongoing	City/Port	7SGSW	Measures) low potential for buried archaeological deposits. (7SGSW ASR, May 2018; 7SGSE ASR, September 2018; FITS ASR, August 2018) Applies to Contractor.
	disturb any human remains, including those interred outside of formal cemeteries?	uncovered at the project site during construction or ground-breaking activities, all work shall immediately halt and the Alameda County Coroner shall be contacted to evaluate the remains, and following the procedures and protocols pursuant to Section 15064.5 (e)(1) of the CEQA Guidelines. If the County Coroner determines that the remains are Native American, the City shall contact the California Native American Heritage Commission (NAHC), pursuant to subdivision (c) of Section 7050.5 of the Health and Safety Code, and all excavation and site preparation activities shall cease within a 50-foot radius of the find until appropriate arrangements are made. If the agencies determine that avoidance is not feasible, then an alternative plan shall be prepared with specific steps and timeframe required to resume construction activities. Monitoring, data recovery, determination of significance and avoidance measures (if applicable) shall be completed expeditiously.	throughout demolition, grading, and/or construction	CRJ/T OIL	7SGSE FITS	Per the 7SGSW ASR, archaeological monitoring was rec ommended where construction pl ans call for excavation between 2 0 to 30 feet below the surface that may penetrate the fill and disturb underlying native sediments where e stable landforms were once present. The locations and depths proposed for archaeological monitoring will be further refined during final design once specific locations and extents are identified for construction elements that extend below the fill. The 7SGSE Project activities limited to the fill deposits will not encounter or disturb intact archaeological deposits. Pilings for the temporary railroad bridge will extend to depths of 140 feet. They will thus penetrate pre-Bay Mud native deposits. While the upper-most San Antonio Formation does have some sensitivity for archaeological sites, the likelihood of encountering and identifying them during coring or drilling is

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE 7SGSW and FITS 7SGSE and FITS 7SGSW 7SGSE N/A

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
					considered low. Native deposits with archaeological sensitivity underlie more recent deposits throughout the APE, and there is some potential for deep excavations (≥ 8 feet) to encounter buried intact archaeological resources. However, the probability of encountering a deeply buried archaeological site in the APE below artificial fill and Bay Muds is probably low. The majority of ground disturbance within the FITS APE is limited to a depth of 24-30 inches for installation of conduit. For the few project elements that have the potential to extend beyond the fill and disturbed deposits and into the Bay Muds and older native deposits, these locations are considered to have low potential for buried archaeological deposits. (7SGSW ASR, Date 2018; 7SGSE ASR, September 2018; FITS ASR, August 2018)
Geology and Soils					September 2010, 1115 ASK, August 2010)
1. Would the project expose people or structures to substantial risk of loss, injury, or death involving: i) Rupture of a known earthquake fault, as delineated on the most recent Alquist-Priolo Earthquake Fault Zoning Map or Seismic	 SCA GEO-2: Soils Report: A preliminary soils report for each construction site within the project area shall be required as part of this project and submitted for review and approval by the Building Services Division. The soils reports shall be based, at least in part, on information obtained from on-site testing. Specifically the minimum contents of the report should include: A. Logs of borings and/or profiles of test pits and trenches: a) The minimum number of borings acceptable, when not used in combination with test pits or trenches, shall be two (2), when in the opinion of the Soils Engineer such borings shall be sufficient to establish a soils profile suitable for the design of all the footings, 	Prior to issuance of demolition, grading or building permit	City/Port	7SGSW 7SGSE FITS	Applies to design phase only. A Geotechnical Investigation Report, including soil testing, has been prepared by Fugro for the 7SGSW Project. Based on the incorporation of geotechnical design recommendations and seismic design criteria for the 7SGSW Project, there project

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring:		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvar/Midgation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
Survey 42 and 117 and Public Resources Code section 2690 et. seq.; ii) Strong seismic ground shaking; iii) Seismicrelated ground failure, including liquefaction, lateral spreading, subsidence, collapse; iv) Landslides?	foundations, and retaining structures. b) The depth of each boring shall be sufficient to provide adequate design criteria for all proposed structures. c) All boring logs shall be included in the soils report. B. Test pits and trenches a) Test pits and trenches shall be of sufficient length and depth to establish a suitable soils profile for the design of all proposed structures. b) Soils profiles of all test pits and trenches shall be included in the soils report. C. A plat shall be included which shows the relationship of all the borings, test pits, and trenches to the exterior boundary of the site. The plat shall also show the location of all proposed site improvements. All proposed improvements shall be labeled. D. Copies of all data generated by the field and/or laboratory testing to determine allowable soil bearing pressures, sheer strength, active and passive pressures, maximum allowable slopes where applicable and any other information which may be required for the proper design of foundations, retaining walls, and other structures to be erected subsequent to or concurrent with work done under the grading permit. E. Soils Report. A written report shall be submitted which shall include, but is not limited to, the following: a) Site description; b) Local and site geology; c) Review of previous field and laboratory investigations for the site; d) Review of information on or in the vicinity of the site on file at the Information Counter, City of Oakland, Office of Planning and Building; e) Site stability shall be addressed with particular attention to existing conditions and proposed corrective attention and retaining structures, resistance to lateral loading, slopes, and specifications, for				would not result in a geologic hazard. (7SGSW Geotech Report, December 2017).

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit		GoPort	Notes (2018 GoPort Technical Studies
Environmental impact	Standard Conditions of Approvar/writigation inteasures	Schedule	Responsibility	Project	References to Mitigation Measures)
	 g) Conclusions and recommendations for temporary and permanent erosion control and drainage. If not provided in a separate report they shall be appended to the required soils report; h) All other items which a Soils Engineer deems necessary; i) The signature and registration number of the Civil Engineer preparing the report. F. The Director of Planning and Building may reject a report that she/he believes is not sufficient. The Director of Planning and Building may refuse to accept a soils report if the certification date of the responsible soils engineer on said document is more than three years old. In this instance, the Director may be require that the old soils report be recertified, that an addendum to the soils report be submitted, or that a new soils report be provided. 				
	a) A site-specific, design level, landslide or liquefaction geotechnical investigation for each construction site within the project area shall be required as part of this project and submitted for review and approval by the Building Services Division. Specifically: i. Each investigation shall include an analysis of expected ground motions at the site from identified faults. The analyses shall be accordance with applicable City ordinances and polices, and consistent with the most recent version of the California Building Code, which requires structural design that can accommodate ground accelerations expected from identified faults. ii. The investigations shall determine final design parameters for the	Prior to issuance of demolition, grading or building permit	City/Port	7SGSW 7SGSE FITS	Applies to design phase only. A Geotechnical Investigation Report has been prepared by Fugro for the 7SGSW Project. A Geotechnical Investigation Report should be prepared for 7SGSE and FITS. (7SGSW Geotech Report, December 2017).
	walls, foundations, foundation slabs, surrounding related improvements, and infrastructure (utilities, roadways, parking lots, and sidewalks). iii. The investigations shall be reviewed and approved by a registered geotechnical engineer. All recommendations by the project engineer, geotechnical engineer, shall be included in the final design, as approved by the City of Oakland. iv. The geotechnical report shall include a map prepared by a land surveyor or civil engineer that shows all field work and location of the "No Build" zone. The map shall include a statement that the locations and limitations of the geologic features are accurate				

Environmental Impact		· ·	Mitigation Implementation/ Monitoring:		Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	placed on this map by the surveyor, the civil engineer or under their supervision, and are accurate to the best of their knowledge. v. Recommendations that are applicable to foundation design, earthwork, and site preparation that were prepared prior to or during the projects design phase, shall be incorporated in the project. vi. Final seismic considerations for the site shall be submitted to and approved by the City of Oakland Building Services Division prior to commencement of the project. vii. A peer review is required for the Geotechnical Report. Personnel reviewing the geologic report shall approve the report, reject it, or withhold approval pending the submission by the applicant or				
	subdivider of further geologic and engineering studies to more adequately define active fault traces. b) Tentative Tract or Parcel Map approvals shall require, but not be limited to, approval of the Geotechnical Report. Mitigation 4.13-1: Redevelopment elements shall be designed in accordance	Prior to issuance	City/Port	7SGSW	Applies to design phase only.
	with criteria established by the IBC, soil investigation and construction requirements established in the Oakland General Plan, the Bay Conservation and Development Commission Safety of Fill Policy, and wharf design criteria established by the Port or City of Oakland (depending on the location of the wharf). The IBC requires structures in the San Francisco Bay Area to be designed to withstand a ground acceleration of 0.4 g or the most current standard. A licensed engineer should monitor construction activities to ensure that the design and	of demolition, grading or building permit	City/Tott	7SGSW 7SGSE FITS	A Geotechnical Investigation Report has been prepared by Fugro for the 7SGSW Project. It includes applicable site-specific recommendations and requirements for the project.
	construction criteria are followed. The Health and Safety element of the Oakland General Plan requires a soils and geologic report be submitted to the Department of Public Works (DPW) prior to the issuance of any building permit. The Oakland General Plan also requires all structures of three or more stories to be supported on pile foundations that penetrate Bay Mud deposits, and to be anchored in firm, non-compressible materials unless geotechnical findings indicate a more appropriate design. The General Plan also provides for the identification and evaluation of existing structural hazards and abatement of those hazards to acceptable levels of risk. To comply with the BCDC safety of fill policy, the plans and specifications for the placement of Bay fill will be submitted to the BCDC Engineering Criteria Review Board for review and approval.				(7SGSW Geotech Report, December 2017).

Environmental Import	Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring:		GoPort	Notes (2018 GoPort Technical Studies			
Environmental Impact	Standard Conditions of Approvar/Midgation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)			
	The Port of Oakland has developed wharf design criteria to be used in the design, construction, reconstruction, and repairs of existing and future wharf structures, except in the event that current engineering practice requires adjustments or modification of the wharf design criteria. All construction associated with New Berth 21 must adhere to the wharf design criteria established by the Port of Oakland. A licensed engineer should monitor construction activities to ensure that the design and construction criteria are followed. The City shall adopt wharf design criteria and apply them to any wharf in the City's jurisdiction.							
	Mitigation 4.13-2: Redevelopment elements shall be designed and constructed in accordance with requirements of a site-specific geotechnical evaluation. Site-specific geotechnical, soils, and foundation investigation reports shall be prepared by a licensed geotechnical or soil engineer experienced in construction methods on fill materials in an active seismic area. The reports shall provide site-specific construction methods and recommendations regarding grading activities, fill placement, compaction, foundation construction, drainage control (both surface and subsurface), and seismic safety. Designers and contractors shall comply with recommendations in the reports. A licensed geotechnical or soil engineer shall monitor earthwork and construction activities to ensure that recommended site-specific construction methods are followed. The Oakland General Plan requires all structures of three or more stories to be supported on pile foundations that penetrate Bay Mud deposits and to be anchored in firm, non-compressible materials unless geotechnical findings indicate a more appropriate design. The General Plan also provides for the identification and evaluation of existing structural hazards and abatement of those hazards to acceptable levels of risk.	Prior to issuance of demolition, grading or building permit	City/Port	7SGSW 7SGSE FITS	Applies to design phase and Contractor. A Geotechnical Investigation Report has been prepared by Fugro for the 7SGSW Project. (7SGSW Geotech Report, December 2017).			
2. Would the project result in substantial soil	See Hydrology and Water Quality section below for SCA HYD-1 through SCA HYD-4							
1 3	 SCA GEO-1: Erosion and Sedimentation Control Plan: Prior to issuance of a demolition, grading, or building permit. A. The project applicant shall obtain a grading permit if required by the Oakland Grading Regulations pursuant to Section 15.04.660 of the Oakland Municipal Code. The grading permit application shall include an erosion and sedimentation control plan for review and approval by the Building Services Division. The erosion and sedimentation control plan shall include all necessary measures to be taken to prevent excessive stormwater runoff or carrying by stormwater runoff of solid materials on to lands of adjacent property owners, public streets, or to creeks as a result 	Prior to issuance of a demolition, grading, or building permit; and ongoing throughout and construction activities (refer to SCA language to the left)	City/Port	7SGSW 7SGSE	Applies to Contractor. Per the 7SGSW and 7SGSE NES, the 7SGSW and 7SGSE Projects shall adhere to SCA GEO-1. SCA GEO-1 was not determined applicable for the FITS Project. (7SGW NES, May 2018; 7SGSE NES, May 2018; FITS Bio Memo, June 2018).			

Environmental Impact	Standard Conditions of Approval/Mitigation Measures		Mitigation Implementation/ Monitoring:		Notes (2018 GoPort Technical Studies	
Environmental Impact	Standard Conditions of Approvar/Midgation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)	
	of conditions created by grading operations. The plan shall include, but not be limited to, such measures as short-term erosion control planting, waterproof slope covering, check dams, interceptor ditches, benches, storm drains, dissipation structures, diversion dikes, retarding berms and barriers, devices to trap, store and filter out sediment, and stormwater retention basins. Off-site work by the project applicant may be necessary. The project applicant shall obtain permission or easements necessary for off-site work. There shall be a clear notation that the plan is subject to changes as changing conditions occur. Calculations of anticipated stormwater runoff and sediment volumes shall be included, if required by the Director of Development or designee. The plan shall specify that, after construction is complete, the project applicant shall ensure that the storm drain system shall be inspected and that the project applicant shall clear the system of any debris or sediment. Ongoing throughout and construction activities B. The project applicant shall implement the approved erosion and sedimentation plan. No grading shall occur during the wet weather season (October 15 through April 15) unless specifically authorized in writing by the Building Services Division.					
3. Would the project be located on expansive soil, as defined in section 1802.3.2 of the California Building Code (2007, as it may be revised), creating substantial risks to life or property?	See above for SCA GEO-2 and SCA GEO-3					
4. Would the project be located above a well,	See above for SCA GEO-2 and SCA GEO-3 and Mitigation Measure 4.13-2					
pit, swamp, mound, tank vault, or unmarked sewer line, creating substantial risks to life or property?	Mitigation 4.13-4: The project applicant shall thoroughly review available building and environmental records. The City and Port shall keep a record of, and the designer shall review, available plans, and facility, building, and environmental records in order to identify underground utilities and facilities, so that these may be either avoided or incorporated into design as relevant.	Prior to issuance of demolition, grading or building permit; and on-going	City/Port	7SGSW 7SGSE FITS	Applies to design phase only.	

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring:	GoPort	(2016 Gol of t Technical Studies	
Environmental impact	Standard Conditions of Approvar/windgation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	Mitigation 4.13-5: The developer shall perform due diligence, including without limitation, retaining the services of subsurface utility locators and other technical experts prior to any ground-disturbing activities. The contractor shall utilize Underground Service Alert or other subsurface utility locators to identify and avoid underground utilities and facilities during construction of redevelopment elements. The contractor shall keep a record of its contacts regarding underground features, and shall make these records available to the City or Port upon request. This condition shall be enforced through contract specification.	Prior to issuance of demolition, grading or building permit; and on-going	City/Port	7SGSW 7SGSE FITS	
5. Would the project be located above landfills for which there is no approved closure or post-closure plan, or unknown fill soils, creating substantial risks to life or property?	See above for SCA-GEO-2 and Mitigation Measures 4.13-2, 4.13-4, and 4.13	-5		N/A	The GoPort projects would not be constructed above a landfill.
Greenhouse Gas Emissions					
1. Would the project generate greenhouse gas emissions, either directly or indirectly, that may have a significant impact on the environment?	SCA GCC-1: Greenhouse Gas (GHG) Reduction Plan: The project applicant shall retain a qualified air quality consultant to develop a Greenhouse Gas (GHG) Reduction Plan for City review and approval. The applicant shall implement the approved GHG Reduction Plan. The goal of the GHG Reduction Plan shall be to increase energy efficiency and reduce GHG emissions by at least 20 percent, with a goal of 36 percent below the project's "adjusted" baseline GHG emissions (as explained below) to help achieve the City's goal of reducing GHG emissions. The GHG Reduction Plan shall include, at a minimum, (a) a detailed GHG emissions inventory for the project under a "business-as-usual" scenario with no consideration of project design features, or other energy efficiencies, (b) an "adjusted" baseline GHG emissions inventory for the project, taking into consideration energy efficiencies included as part of the project (including the City's Standard Conditions of Approval, proposed mitigation measures, project design features, and other City requirements), (c) a comprehensive set of quantified additional GHG reduction measures available to further reduce GHG emissions beyond the adjusted GHG emissions, and (d) requirements for ongoing monitoring and reporting to demonstrate that the additional GHG reduction measures are being implemented. If the project is to be constructed in phases, the GHG Reduction Plan shall provide GHG emission scenarios by phase.	Prior to approval of PUD.	City/Port	N/A	GHG for buildings.

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE 7SGSW and FITS 7SGSW and FITS 7SGSW

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvaminingation incastings	Schedule	Responsibility	Project	References to Mitigation Measures)
	Specifically, the applicant/sponsor shall adhere to the following:				
	a) <i>GHG Reduction Measures Program</i> . Prepare and submit to the City Planning Director or his/her designee for review and approval a GHG Reduction Plan that specifies and quantifies GHG reduction measures that the project will implement by phase.				
	Potential GHG reduction measures to be considered include, but are not be limited to, measures recommended in BAAQMD's latest CEQA Air Quality Guidelines, the California Air Resources Board Scoping Plan (December 2008, as may be revised), the California Air Pollution Control Officers Association (CAPCOA) Quantifying Greenhouse Gas Mitigation Measures Document (August 2010, as may be revised), the California Attorney General's website, and Reference Guides on Leadership in Energy and Environmental Design (LEED) published by the U.S. Green Building Council.				
	The proposed GHG reduction measures must be reviewed and approved by the City Planning Director or his/her designee. The types of allowable GHG reduction measures include the following (listed in order of City preference): (1) physical design features; (2) operational features; and (3) the payment of fees to fund GHG-reducing programs (i.e., the purchase of "offset carbon credits," pursuant to item "b" below).				
	The allowable locations of the GHG reduction measures include the following (listed in order of City preference): (1) the project site; (2) offsite within the City of Oakland; (3) off-site within the San Francisco Bay Area Air Basin; (4) off-site within the State of California; then (5) elsewhere in the United States.				
	b) Offset Carbon Credits Guidelines. For GHG reduction measures involving the purchase of offset carbon credits, evidence of the payment/purchase shall be submitted to the City Planning Director or his/her designee for review and approval prior to completion of the project (or prior to completion of the project phase, if the project includes more one phase).				
	As with preferred locations for the implementation of all GHG reductions measures, the preference for offset carbon credit purchases include those that can be achieved as follows (listed in order of City preference): (1) within the City of Oakland; (2) within the San Francisco Bay Area Air Basin; (3) within the State of California; then (4) elsewhere in the United				

7SGSE

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE

7SGSW and FITS

7SGSE and FITS

FITS

7SGSW

7SGSE

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit	=	GoPort	Notes (2018 GoPort Technical Studies	
Environmental impact		Schedule	Responsibility	Project	References to Mitigation Measures)	
		States. The cost of offset carbon credit purchases shall be based on current market value at the time purchased and shall be based on the Project's operational emissions estimated in the GHG Reduction Plan or subsequent approved emissions inventory, which may result in emissions that are higher or lower than those estimated in the GHG Reduction Plan.				
	c)	Plan Implementation and Documentation. For physical GHG reduction measures to be incorporated into the design of the project, the measures shall be included on the drawings submitted for construction-related permits. For operational GHG reduction measures to be incorporated into the project, the measures shall be implemented on an indefinite and ongoing basis beginning at the time of project completion (or at the completion of the project phase for phased projects).				
		For physical GHG reduction measures to be incorporated into off-site projects, the measures shall be included on drawings and submitted to the City Planning Director or his/her designee for review and approval and then installed prior to completion of the subject project (or prior to completion of the project phase for phased projects). For operational GHG reduction measures to be incorporated into off-site projects, the measures shall be implemented on an indefinite and ongoing basis beginning at the time of completion of the subject project (or at the completion of the project phase for phased projects).				
	d)	Compliance, Monitoring and Reporting. Upon City review and approval of the GHG Reduction Plan program by phase, the applicant/sponsor shall satisfy the following requirements for ongoing monitoring and reporting to demonstrate that the additional GHG reduction measures are being implemented. The GHG Reduction Plan requires regular periodic evaluation over the life of the Project (generally estimated to be at least 40 years) to determine how the Plan is achieving required GHG emissions reductions over time, as well as the efficacy of the specific additional GHG reduction measures identified in the Plan.				
		Implementation of the GHG reduction measures and related requirements shall be ensured through the project applicant/sponsor's compliance with Conditions of Approval adopted for the project. Generally, starting two years after the City issues the first Certificate of Occupancy for the project, the project applicant/sponsor shall prepare each year of the useful life of the project an Annual GHG Emissions Reduction Report (Annual Report), subject to the City Planning Director or his/her designee for review and approval. The Annual Report shall be submitted to an independent reviewer of the City Planning Director's or his/her designee's				

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE 7SG

7SGSW and FITS

7SGSE and FITS

FITS

7SGSW

7SGSE

Environmental Impact		Standard Conditions of Approval/Mitigation Measures	Mitigation Imp Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact		Schedule	Responsibility	Project	References to Mitigation Measures)	
		choosing, to be paid for by the project applicant/sponsor (see <i>Funding</i> , below), within two months of the anniversary of the Certificate of Occupancy.				
		The Annual Report shall summarize the project's implementation of GHG reduction measures over the preceding year, intended upcoming changes, compliance with the conditions of the Plan, and include a brief summary of the previous year's Annual Report results (starting the second year). The Annual Report shall include a comparison of annual project emissions to the baseline emissions reported in the GHG Plan.				
		The GHG Reduction Plan shall be considered fully attained when project emissions are 36 percent below the project's "adjusted" baseline GHG emissions, as confirmed by the City Planning Director or his/her designee through an established monitoring program unless the applicant demonstrates it is infeasible to achieve the 36 percent goal. Monitoring and reporting activities will continue at the City's discretion, as discussed below.				
		Funding. Within two months after the Certificate of Occupancy, the project applicant/sponsor shall fund an escrow-type account or endowment fund to be used exclusively for preparation of Annual Reports and review and evaluation by the City Planning Director or his/her designee, or its selected peer reviewers. The escrow-type account shall be initially funded by the project applicant/sponsor in an amount determined by the City Planning Director or his/her designee and shall be replenished by the project applicant/sponsor so that the amount does not fall below an amount determined by the City Planning Director or his/her designee. The mechanism of this account shall be mutually agreed upon by the project applicant/sponsor and the City Planning Director or his/her designee, including the ability of the City to access the funds if the project applicant/sponsor is not complying with the GHG Reduction Plan requirements, and/or to reimburse the City for its monitoring and enforcement costs.				
		Corrective Procedure. If the third Annual Report, or any report thereafter, indicates that, in spite of the implementation of the GHG Reduction Plan, the project is not achieving the GHG reduction goal, the project applicant/sponsor shall prepare a report for City review and approval, which proposes additional or revised GHG measures to better achieve the GHG emissions reduction goals, including without limitation, a discussion on the feasibility and effectiveness of the menu of other additional measures (Corrective GHG Action Plan). The project				

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE

7SGSW and FITS

7SGSE and FITS

FITS

7SGSW

7SGSE

Environmental Impact		Standard Conditions of Approval/Mitigation Measures	Mitigation Imp Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental impact	Standard Conditions of Approval Midgation Medicales	Schedule	Responsibility	Project	References to Mitigation Measures)	
		applicant/sponsor shall then implement the approved Corrective GHG Action Plan.				
		If, one year after the Corrective GHG Action Plan is implemented, the required GHG emissions reduction target is still not being achieved, or if the project applicant/owner fails to submit a report at the times described above, or if the reports do not meet City requirements outlined above, the City Planning Director or his/her designee may, in addition to its other remedies, (a) assess the project applicant/sponsor a financial penalty based upon actual percentage reduction in GHG emissions as compared to the percent reduction in GHG emissions established in the GHG Reduction Plan; or (b) refer the matter to the City Planning Commission for scheduling of a compliance hearing to determine whether the project's approvals should be revoked, altered or additional conditions of approval imposed.				
		The penalty as described in (a) above shall be determined by the City Planning Director or his/her designee and be commensurate with the percentage GHG emissions reduction not achieved (compared to the applicable numeric significance thresholds) or required percentage reduction from the "adjusted" baseline.				
		In determining whether a financial penalty or other remedy is appropriate, the City shall not impose a penalty if the project applicant/sponsor has made a good faith effort to comply with the GHG Reduction Plan.				
		The City would only have the ability to impose a monetary penalty after a reasonable cure period and in accordance with the enforcement process outlined in Planning Code Chapter 17.152. If a financial penalty is imposed, such penalty sums shall be used by the City solely toward the implementation of the GHG Reduction Plan.				
	g)	<i>Timeline Discretion and Summary.</i> The City Planning Director or his/her designee shall have the discretion to reasonably modify the timing of reporting, with reasonable notice and opportunity to comment by the applicant, to coincide with other related monitoring and reporting required for the project.				
		• Fund Escrow-type Account for City Review: Certificate of Occupancy plus 2 months				
		 Submit Baseline Inventory of "Actual Adjusted Emissions": Certificate of Occupancy plus 1 year Submit Annual Report #1: Certificate of Occupancy plus 2 years 				

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit	=	GoPort	Notes (2018 GoPort Technical Studies
Environmentai impact		Schedule	Responsibility	Project	References to Mitigation Measures)
	 Submit Corrective GHG Action Plan (if needed): Certificate of Occupancy plus 4 years (based on findings of Annual Report #3) Post Attainment Annual Reports: Minimum every 3 years and at the City Planning Director's or his/her designee's reasonable discretion 				
Hazards and Hazardous M	1aterials				
1. Would the project create a significant hazard to the public or the environment through reasonably foreseeable upset and accident conditions involving the release of hazardous materials into the environment?	SCA HAZ-1: Best Management Practices for Soil and Groundwater Hazards The project applicant shall implement all of the following Best Management Practices (BMPs) regarding potential soil and groundwater hazards. a) Soil generated by construction activities shall be stockpiled onsite in a secure and safe manner or if designated for off-site disposal at a permitted facility, the soil shall be loaded, transported and disposed of in a safe and secure manner. All contaminated soils determined to be hazardous or non-hazardous waste must be adequately profiled (sampled) prior to acceptable reuse or disposal at an appropriate off-site facility. Specific sampling and handling and transport procedures for reuse or disposal shall be in accordance with applicable local, state and federal agencies laws, in particular, the Regional Water Quality Control Board (RWQCB) and/or the Alameda County Department of Environmental Health (ACDEH) and policies of the City of Oakland. The excavation, on-site management, and off-site disposal of soil from Project areas within the OARB shall follow the DTSC-approved RAP/RMP.	Ongoing throughout demolition, grading, and construction activities.	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. Phase II recommended for all projects. It was determined that the 7SGSW and FITS Project feature environmental conditions which could pose a low, medium and high-risk. The 7SGSE was features environmental conditions which could pose a low and medium-risk due. A Phase II Site Investigation and Construction Risk Management Plan is recommended.
	 b) Groundwater pumped from the subsurface shall be contained onsite in a secure and safe manner, prior to treatment and disposal, to ensure environmental and health issues are resolved pursuant to applicable laws and policies of the City of Oakland, the RWQCB and/or the ACDEH. The on-site management and off-site disposal of groundwater extracted from Project areas within the OARB shall follow the DTSC-approved RAP/RMP for Project areas within the OARB. Engineering controls shall be utilized, which include impermeable barriers to prohibit groundwater and vapor intrusion into the building (pursuant to the Standard Condition of Approval regarding Radon or Vapor Intrusion from Soil and Groundwater Sources. c) Prior to issuance of any demolition, grading, or building permit, the applicant shall submit for review and approval by the City of Oakland, written verification that the appropriate federal, state or county oversight authorities, including but not limited to the RWQCB and/or the ACDEH, have granted all required clearances and confirmed that the all applicable standards, regulations and conditions for all previous contamination at the 				(7SGSW ISA, April 2018; 7SGSE ISA, April 2018; FITS ISA, July 2018).

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit		GoPort	Notes (2018 GoPort Technical Studies		
Environmentai impact		Schedule	Responsibility	Project	References to Mitigation Measures)		
		site. The applicant also shall provide evidence from the City's Fire Department, Office of Emergency Services, indicating compliance with the Standard Condition of Approval requiring a Site Review by the Fire Services Division pursuant to City Ordinance No. 12323, and compliance with the Standard Condition of Approval requiring a Phase I and/or Phase II Reports.					
	and imp	A HAZ-2: Hazards Best Management Practices: The project applicant construction contractor shall ensure Best Management Practices (BMPs) are elemented as part of construction to minimize the potential negative effects groundwater and soils. These shall include the following:	Prior to commencement of demolition, grading, or	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. Phase II was recommended for all projects.	
	a)	Follow manufacture's recommendations on use, storage, and disposal of chemical products used in construction;	construction.			It was determined that the	
	b)	Avoid overtopping construction equipment fuel gas tanks;				7SGSW and FITS Project feature environmental conditions which	
	c)	During routine maintenance of construction equipment, properly contain and remove grease and oils;					could pose a low, medium and high-risk. The 7SGSE was
	d)	Properly dispose of discarded containers of fuels and other chemicals.				features environmental conditions which could pose a low and	
	e)	Ensure that construction would not have a significant impact on the environment or pose a substantial health risk to construction workers and the occupants of the proposed development. Soil sampling and chemical analyses of samples shall be performed to determine the extent of potential contamination beneath all USTs, elevator shafts, clarifiers, and subsurface hydraulic lifts when on-site demolition, or construction activities would potentially affect a particular development or building.				medium-risk due. A Phase II Site Investigation and Construction Risk Management Plan is recommended. (7SGSW ISA, April 2018; 7SGSE ISA, April 2018; FITS ISA, July 2018).	
	f)	If soil, groundwater or other environmental medium with suspected contamination is encountered unexpectedly during construction activities (e.g., identified by odor or visual staining, or if any underground storage tanks, abandoned drums or other hazardous materials or wastes are encountered), the applicant shall cease work in the vicinity of the suspect material, the area shall be secured as necessary, and the applicant shall take all appropriate measures to protect human health and the environment. Appropriate measures shall include notification of regulatory agency(ies) and implementation of the actions described in the City's Standard Conditions of Approval (and DTSC-approved RAP/RMP for Project area within the OARB), as necessary, to identify the nature and extent of contamination. Work shall not resume in the area(s) affected until the measures have been implemented under the oversight of the City or regulatory agency, as appropriate.					

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmentai impact	Standard Conditions of Approvar/Midgation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	SCA HAZ-3: Hazardous Materials Business Plan: The project applicant shall submit a Hazardous Materials Business Plan for review and approval by Fire Prevention Bureau, Hazardous Materials Unit. Once approved this plan shall be kept on file with the City and will be updated as applicable. The purpose of the Hazardous Materials Business Plan is to ensure that employees are adequately trained to handle the materials and provides information to the Fire Services Division should emergency response be required. The Hazardous Materials Business Plan shall include the following: a) The types of hazardous materials or chemicals stored and/or used on site, such as petroleum fuel products, lubricants, solvents, and cleaning fluids. b) The location of such hazardous materials. c) An emergency response plan including employee training information. d) A plan that describes the manner in which these materials are handled, transported and disposed.	Prior to issuance of a business license.	City/Port	N/A	Only applicable for business license.
2. Would the project create a significant hazard to the public through the storage or use of acutely hazardous materials near sensitive receptors?	See above for SCA HAZ-1 and SCA HAZ-2				
3. Would the project be located on a site which is included on a list of hazardous materials sites compiled pursuant to Government Code Section 65962.5 (i.e.,the "Cortese List") and, as a result, would create a significant	SCA HAZ-4: Asbestos Removal in Structures: If asbestos-containing materials (ACM) are found to be present in building materials to be removed, demolished and disposed of, the project applicant shall submit specifications signed by a certified asbestos consultant for the removal, encapsulation, or enclosure of the identified ACM in accordance with all applicable laws and regulations, including but not necessarily limited to: California Code of Regulations, Title 8; Business and Professions Code; Division 3; California Health & Safety Code 25915-25919.7; and Bay Area Air Quality Management District, Regulation 11, Rule 2, as may be amended.	Prior to issuance of a demolition permit.	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. Phase II was recommended for all projects.
hazard to the public or the environment.	SCA HAZ-5: Lead-Based Paint/Coatings, Asbestos, or PCB Occurrence Assessment: The project applicant shall submit a comprehensive assessment report to the Fire Prevention Bureau, Hazardous Materials Unit, signed by a qualified environmental professional, documenting the presence or lack thereof of asbestos-containing materials (ACM), lead-based paint, and any other	Prior to issuance of any demolition, grading or building permit	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. Phase II was recommended for all projects.

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring:		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Midgation Measures	Schedule	Responsibility	Project	
	building materials or stored materials classified as hazardous waste by State or federal law.				
	SCA HAZ-6: Lead-based Paint Remediation: If lead-based paint is present, the project applicant shall submit specifications to the Fire Prevention Bureau, Hazardous Materials Unit signed by a certified Lead Supervisor, Project Monitor, or Project Designer for the stabilization and/or removal of the identified lead paint in accordance with all applicable laws and regulations, including but not necessarily limited to: Cal/OSHA's Construction Lead Standard, 8 CCR1532.1 and DHS regulation 17 CCR Sections 35001 through 36100, as may be amended.	Prior to issuance of any demolition, grading or building permit.	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. Phase II was recommended for all projects.
	SCA HAZ-7: Other Materials Classified as Hazardous Waste: If other materials classified as hazardous waste by State or federal law are present, the project applicant shall submit written confirmation to Fire Prevention Bureau, Hazardous Materials Unit that all State and federal laws and regulations shall be followed when profiling, handling, treating, transporting and/or disposing of such materials.	Prior to issuance of any demolition, grading or building permit.	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. Phase II was recommended for all projects.
	SCA HAZ-8: Health and Safety Plan per Assessment: If the required lead-based paint/coatings, asbestos, or PCB assessment finds presence of such materials, the project applicant shall create and implement a health and safety plan to protect workers from risks associated with hazardous materials during demolition, renovation of affected structures, and transport and disposal.	Prior to issuance of any demolition, grading or building permit.	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. Phase II was recommended for all projects.
	Mitigation 4.7-3: Implement RAP/RMP as approved by DTSC, and if future use proposals include uses not identified in the Reuse Plan and incorporated into the RAP/RMP or if future amendments to the remediation requirements are proposed, obtain DTSC and, as required, City approval.	Prior to issuance of any demolition, grading or building permit; and on-going	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. The RAP/RMP applies to the OAB portions of all projects.
	Mitigation 4.7-4: For the project areas not covered by the DTSC-approved RAP/RMP, investigate potentially contaminated sites; if contamination is found, assess potential risks to human health and the environment, prepare and implement a clean up plan for DTSC or RWQCB approval, prepare and implement a Risk Management Plan and prepare and implement a Site Health and Safety Plan prior to commencing work. Since implementation of the RAP/RMP approved by DTSC is proposed as part of the project for the OARB, and the RAP/RMP requires remediation to be fully protective of human health and the environment for the proposed future uses of	Prior to issuance of any demolition, grading or building permit; and on-going	City/Port	7SGSW 7SGSE FITS	Applies to Contractor.

Environmental Impact	Standard Conditions of Annuavel/Mitigation Magazines	Mitigation Im Monit	-	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	the OARB, no further mitigation is required for the OARB unless either (1) future use proposals include those that were not identified in the Reuse Plan and incorporated into the RAP/RMP or (2) future amendments are proposed to the remediation requirements included in the approved RAP/RMP. In either of these two circumstances, required remediation includes obtaining the DTSC and, as required, City approval, for proposed changes in full conformance with applicable legal requirements including but not limited to the HSAA and CEQA.				
	Specific contaminants and concentrations may vary across the redevelopment project area. Nevertheless, the types of impacts expected, and therefore, the general response actions and approaches to mitigation would be consistent throughout the redevelopment project area. With respect to the OARB and as described in greater detail above, the process across the redevelopment project area would mirror the RAP/RMP process that is already underway at the OARB. With respect to the OARB sub-district, pursuant to HSAA Chapter 6.8, the OBRA has proposed a RAP/RMP. The OBRA's remedial goal is to remediate soil and groundwater contamination consistent with the City of Oakland ULR Program 10 ⁻⁵ remedy with appropriate land use restrictions. This RAP/RMP must be approved by DTSC, which has the legal discretion to impose remedies falling within the 10 ⁻⁴ and 10 ⁻⁶ risk range.				
	For the other sub-districts and areas not included in the DTSC-approved RAP/RMP, prior to beginning redevelopment-related activities, potentially affected areas shall be investigated, potentially including additional studies or site characterization activities, as required by the regulatory agencies (DTSC or RWQCB). Once contaminated areas are identified, potential human health risks from contaminants of concern based upon realistic future land use shall be assessed, health risk-based and environmental risk-based cleanup goals shall be established, and a determination regarding the need for additional site assessment work shall be made.				
	The potential risks associated with affected areas shall be assessed in accordance with regulatory agency guidance and approvals and may result in remediation requirements. Such cleanup plans shall address each area where soil or groundwater is contaminated above ULR goals could be encountered during redevelopment. The clean up plan, the names of which vary based on the type and source of contamination and the legal framework for the particular oversight agency, shall specify measures to be taken to protect workers and the public from exposure to potential contamination and certify that the proposed remediation measures, including removal, disposal, stabilization and/or institutional controls are protective of human health and the environment and implemented in accordance with federal, state and local requirements. Additionally, a Risk Management Plan may be required by the oversight agency to address site redevelopment activities and operations and provide an				

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring:		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvar/Midgation Measures	Schedule	Responsibility	Project	
	enforcement structure to be in place during and post-construction. Finally, a Site Health and Safety Plan shall be prepared in accordance with the OSHA and Cal/OSHA regulations. Off-hauling of contamination shall comply with applicable laws, and construction hours shall be limited as provided for in SCA NOI-1 through SCA NOI-6 in order to prevent night-time glare. Additionally, potential odor impact measures, and dust or other nuisance conditions from remediation-related truck traffic is provided for in Mitigation Measure 4.3-13, and safety concerns are addressed in Mitigation Measure 4.9-3.				
	Mitigation 4.7-5: For the project areas not covered by the DTSC-approved RAP/RMP, remediate soil and groundwater contamination consistent with the City of Oakland ULR Program and other applicable laws and regulations. The City of Oakland ULR Program has determined that reducing the target risk level to 1x10-5 for commercial or industrial land uses in combination with appropriate institutional controls would reduce the risk to future residents, employees, and visitors to less than significant. Within the OARB area covered by the DTSC-approved RAP/RMP, implementation will result in avoidance of any potentially significant impact to future commercial/industrial/maritime/utility workers, and site visitors. Moreover, the measures required for the areas not covered by the DTSC-approved RAP/RMP, (Measure 4.7-4) would evaluate and control potential human health risks from contaminants of concern in the redevelopment project area and will sufficiently address this potential impact. In addition, Mitigation Measures 4.14-1 and 4.14-2, which prohibit the installation of groundwater wells for any purpose other than construction de-watering and remediation and require that even for construction de-watering and remediation use of those wells be minimized, will reduce the potential for contaminants to migrate to other underlying ground aquifers, thus lessening the impact to future residents, employees and visitors to less than significant.	Prior to issuance of any demolition, grading or building permit; and on-going	City/Port	7SGSW 7SGSE FITS	Applies to Contractor.
	Mitigation 4.7-6: Buildings and structures constructed prior to 1978 slated for demolition or renovation that have not previously been evaluated for the presence of LBP shall be sampled to determine whether LBP is present in painted surfaces, and the safety precautions and work practices as specified in government regulations shall be followed during demolition.	Prior to issuance of any demolition, grading or building permit; and on-going	City/Port	7SGSW 7SGSE FITS	Applies to Contractor.
	Mitigation 4.7-7: Buildings, structures and utilities that have not been surveyed for ACM, shall be surveyed to determine whether ACM is present prior to demolition or renovation, and the safety precautions and work practices as specified in government regulations shall be followed during demolition.	Prior to issuance of any demolition, grading or building permit; and on-going	City/Port	7SGSW 7SGSE FITS	Applies to Contractor.

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Printigation vicasures	Schedule	Responsibility	Project	References to Mitigation Measures)
	Mitigation 4.7-8: Buildings and structures proposed for demolition or renovation shall be surveyed for PCB-impacted building materials, and the safety precautions and work practices as specified in government regulations shall be followed during demolition.	Prior to issuance of any demolition, grading or building permit; and on-going	City/Port	7SGSW 7SGSE FITS	Applies to Contractor.
	Mitigation 4.7-9: For above-ground and underground storage tanks (ASTs/USTs) on the OARB, implement the RAP/RMP.	Prior to issuance of any demolition, grading or building permit; and on-going	City/Port	N/A	Storage tanks are not applicable for the GoPort projects.
	Mitigation 4.7-11 : For LBP-impacted ground on the OARB, implementation of RAP/RMP to be approved by DTSC as part of the project will result in avoidance of this potentially significant impact. For the remainder of the development project area, sampling shall be performed on soil or paved areas around buildings that are known or suspected to have LBP, and the safety precautions and work practices specified in government regulations shall be followed.	Prior to issuance of any demolition, grading or building permit; and on-going	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. Contingent on Phase II results.
	Mitigation 4.7-12: The condition of identified ACM shall be assessed annually, and prior to reuse of a building known to contain ACM.	Prior to issuance of any demolition, grading or building permit; and on-going	City/Port	N/A	Relates to ACM mitigation from interim or future use of existing buildings.
	Mitigation 4.7-13 : No future tenancies shall be authorized at the OARB for use categories that are inconsistent with the Reuse Plan without an updated environmental analysis and DTSC approval as provided for in the RAP/RMP.	Pre-operations	City/Port	N/A	GoPort Project will not affect OARB tenancies.
	For the OARB, baseline environmental analyses have been completed to support current interim uses of existing structures, including numerous commercial, trucking, warehouse and other tenants, the Oakland Military Institute and transitional housing uses for formerly-incarcerated women and their families and for various homeless service providers including an overnight shelter. Other environmental hazards may also be encountered by future interim occupants of existing OARB structures, and completion of a baseline environmental evaluation to identify and abate such hazards prior to occupancy by tenants will mitigate such hazards.				

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring:		GoPort	Notes (2018 GoPort Technical Studies
,		Schedule	Responsibility	Project	References to Mitigation Measures)
	Interim occupancy by future tenants who may propose land uses which are inconsistent with the Reuse Plan, and thus may not have been considered in the DTSC-approved RAP/RMP, shall occur only after DTSC approval as provided for in the RAP/RMP in order to assure that such future non-conforming tenants are protected from other environmental hazards. As stated above, for the remainder of the redevelopment project area, any building that has not been surveyed for ACM but potentially contains ACM shall be surveyed to determine whether ACM is present prior to demolition, renovation or reuse.				
	Mitigation 4.7-16: Oil-filled electrical equipment in the redevelopment project area that has not been surveyed shall be investigated prior to the equipment being taken out of service to determine whether PCBs are present. Equipment found to contain PCBs should be part of an ongoing monitoring program. Surface and subsurface contamination from any PCB equipment shall be investigated and remediated in compliance with applicable laws and regulations.	Prior to issuance of any demolition, grading or building permit; and on-going during operations	City/Port	7SGSW 7SGSE FITS	Applies to Contractor.
	Mitigation 4.7-17: PCB-containing or PCB-contaminated equipment taken out of service shall be handled and disposed in compliance with applicable laws and regulations. Equipment filled with dialectic fluid (oil) including transformers, ballast, etc. containing more than 5 ppm PCBs is considered a hazardous waste in California	Prior to issuance of any demolition, grading or building permit; and on-going during operations	City/Port	7SGSW 7SGSE FITS	Applies to Contractor.
4. Would the project fundamentally impair implementation of or physically interfere with an adopted emergency response plan or emergency evacuation plan?	See below in Traffic and Transportation for Mitigation Measures 4.3-8, and	Mitigation Measu	re 3.16-15a and 3.	16-15b	
Hydrology and Water Qua	lity				
	See above in Hazards and Hazardous Materials section for SCA HAZ-1				

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Implemen Monitoring:		GoPort	Notes (2018 GoPort Technical Studies
Environmentai impact	ominate continue of reper of market states	Schedule	Responsibility	Project	References to Mitigation Measures)
1. Would the project violate any water quality standards or waste discharge requirements during inwater construction or encountering shallow groundwater during construction?	SCA HYD-1: Stormwater Pollution Prevention Plan (SWPPP): The project applicant must obtain coverage under the General Construction Activity Storm Water Permit (General Construction Permit) issued by the State Water Resources Control Board (SWRCB). The project applicant must file a notice of intent (NOI) with the SWRCB. The project applicant will be required to prepare a stormwater pollution prevention plan (SWPPP) and submit the plan for review and approval by the Building Services Division. At a minimum, the SWPPP shall include a description of construction materials, practices, and equipment storage and maintenance; a list of pollutants likely to contact stormwater; site-specific erosion and sedimentation control practices; a list of provisions to eliminate or reduce discharge of materials to stormwater; Best Management Practices (BMPs), and an inspection and monitoring program. Prior to the issuance of any construction-related permits, the project applicant shall submit to the Building Services Division a copy of the SWPPP and evidence of submittal of the NOI to the SWRCB. Implementation of the SWPPP shall start with the commencement of construction and continue though the completion of the project. After construction is completed, the project applicant shall submit a notice of termination to the SWRCB.	Prior to and ongoing throughout demolition, grading, and/or construction activities.	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. Measure applies for all projects as an SCA CEQA Mitigation. However, with proper implementation of temporary construction site BMPs, such as temporary erosion control, sediment control, tracking control, and management control measures, short-term water quality impacts during construction would be avoided or minimized.
	Mitigation 4.15-1: Prior to in-water construction, the contractor shall prepare a water quality protection plan acceptable to the RWQCB, including site-specific best management practices for protection of Bay waters, and shall implement this plan during construction. BMPs to effectively control turbidity and/or contaminant suspension and migration would be site-specific. They may include, and are not limited to, the following: • Use environmental or clamshell dredges or hydraulic cutterhead dredges designed to reduce release of solids. • Reduce or eliminate overflow of decant water from barges used to transport material. • Use silt curtains or other specialized equipment to reduce dispersion of material during dredging and filling operations.	Prior to issuance of any demolition, grading or building permit; and on-going during operations	City/Port	N/A	Applies to in-water construction only.
	Mitigation 4.15-2: Contractors and developers shall comply with all permit conditions from the Corps, RWQCB and BCDC. This measure shall be enforced on Contractors by contract specifications.	Prior to issuance of any demolition, grading or building permit; and on-going during operations	City/Port	N/A	

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvar/Midgation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
2. Would the project result in substantial erosion or siltation on- or off-site that would affect the quality of receiving waters?	See above for SCA HYD-1, SCA GEO-1 (Geology and Soils section) and SC Materials)				
3. Would the project result in substantial flooding on- or off-site?	Mitigation 3.9-1: Coordinate and consult with EBMUD and if necessary design and build storm drain improvements resulting from increased elevation in the North Gateway area.	Prior to issuance of building permit (or other construction-related permit).	City/Port	N/A	Not in the North Gateway area.
4. Would the project create or contribute substantial runoff which would exceed the capacity of existing or planned stormwater drainage systems?	SCA HYD-2: Post-Construction Stormwater Management Plan: The applicant shall comply with the requirements of Provision C.3 of the National Pollutant Discharge Elimination System (NPDES) permit issued to the Alameda Countywide Clean Water Program. The applicant shall submit with the application for a building permit (or other construction-related permit) a completed Construction-Permit-Phase Stormwater Supplemental Form to the Building Services Division. The project drawings submitted for the building permit (or other construction-related permit) shall contain a stormwater management plan, for review and approval by the City, to manage stormwater run-off and to limit the discharge of pollutants in stormwater after construction of the project to the maximum extent practicable. a) The post-construction stormwater management plan shall include and identify the following: i. All proposed impervious surface on the site; ii. Anticipated directional flows of on-site stormwater runoff; and iii. Site design measures to reduce the amount of impervious surface area and directly connected impervious surfaces; and iv. Source control measures to limit the potential for stormwater pollution; v. Stormwater treatment measures to remove pollutants from stormwater runoff; and vi. Hydromodification management measures so that post-project stormwater runoff does not exceed the flow and duration of pre-project runoff, if required under the NPDES permit.	Prior to issuance of building permit (or other construction-related permit). Prior to final permit inspection, the applicant shall also implement the approved stormwater management plan.	City/Port	7SGSW 7SGSE FITS	Applies to design phase only. No anticipated increases in stormwater runoff flow for the FITS, 7SGSE or 7SGSW Projects because the Project improvements would have a net decrease of impervious surface. (FITS WQR, June 2018; 7SGSE AQR, May 2018; 7SGSW, May 2018).

Environmental Impact	Standard Conditions of Annuaral/Mitigation Magazines	Mitigation Im Monit	=	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	 i. Detailed hydraulic sizing calculations for each stormwater treatment measure proposed; and ii. Pollutant removal information demonstrating that any proposed manufactured/mechanical (i.e., non-landscape-based) stormwater treatment measure, when not used in combination with a landscape-based treatment measure, is capable or removing the range of pollutants typically removed by landscape-based treatment measures and/or the range of pollutants expected to be generated by the project. All proposed stormwater treatment measures shall incorporate appropriate planting materials for stormwater treatment (for landscape-based treatment measures) and shall be designed with considerations for vector/mosquito control. Proposed planting materials for all proposed landscape-based stormwater treatment measures shall be included on the landscape and irrigation plan for the project. The applicant is not required to include on-site stormwater treatment measures in the post-construction stormwater management plan if he or she secures approval from Planning and Zoning of a proposal that demonstrates compliance with the requirements of the City's Alternative Compliance Program. 				
	 SCA HYD-3: Maintenance Agreement for Stormwater Treatment Measures: For projects incorporating stormwater treatment measures, the applicant shall enter into the "Standard City of Oakland Stormwater Treatment Measures Maintenance Agreement," in accordance with Provision C.3.e of the NPDES permit, which provides, in part, for the following: i. The applicant accepting responsibility for the adequate installation/construction, operation, maintenance, inspection, and reporting of any on-site stormwater treatment measures being incorporated into the project until the responsibility is legally transferred to another entity; and ii. Legal access to the on-site stormwater treatment measures for representatives of the City, the local vector control district, and staff of the Regional Water Quality Control Board, San Francisco Region, for the purpose of verifying the implementation, operation, and maintenance of the on-site stormwater treatment measures and to take corrective action if necessary. The agreement shall be recorded at the County Recorder's Office at the applicant's expense. 	Prior to final zoning inspection.	City/Port	7SGSW 7SGSE FITS	Applies to design phase only. No anticipated increases in storm water runoff flow for the FITS, 7SGSE or 7SGSW Projects because the Project improvements would have a net decrease of impervious surface. (FITS WQR, June 2018; 7SGSE AQR, May 2018; 7SGSW, May 2018).
	SCA HYD-4: Stormwater and Sewer: Confirmation of the capacity of the City's surrounding stormwater and sanitary sewer system and state of repair shall be completed by a qualified civil engineer with funding from the project applicant. The project applicant shall be responsible for the necessary	Prior to completing the final design for	City/Port	7SGSW 7SGSE FITS	Applies to design phase only. No anticipated increases in storm water runoff flow for the FITS,

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE 7SGSW and FITS 7SGSE and FITS 7SGSW 7SGSE N/A

Engineers and Lumpak	Shouland Conditions of Assessed Militiastics Manager	Mitigation Im Monite	=	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	stormwater and sanitary sewer infrastructure improvements to accommodate the proposed project. In addition, the applicant shall be required to pay additional fees to improve sanitary sewer infrastructure if required by the Sewer and Stormwater Division. Improvements to the existing sanitary sewer collection system shall specifically include, but are not limited to, mechanisms to control or minimize increases in infiltration/inflow to offset sanitary sewer increases associated with the proposed project. To the maximum extent practicable, the applicant will be required to implement Best Management Practices to reduce the peak stormwater runoff from the project site. Additionally, the project applicant shall be responsible for payment of the required installation or hookup fees to the affected service providers.	the project's sewer service.			7SGSE or 7SGSW Projects because the Project improveents would have a net decrease of imp ervious surface. (FITS WQR, June 2018; 7SGSE AQR, May 2018; 7SGSW, May 2018).
5. Would the project	See above for SCA HYD-1 through SCA HYD-3 and SCA GEO-1 (Geology	and Soils section)			
create or contribute substantial runoff which would be an additional source of polluted runoff?	Mitigation 4.15-5: Post-construction controls of stormwater shall be incorporated into the design of new redevelopment elements to reduce pollutant loads. NPDES permitting requires that BMPs to control post-construction stormwater be implemented to the maximum extent practicable. Analysis of anticipated runoff volumes and potential effects to receiving water quality from stormwater shall be made for specific redevelopment elements, and site-specific BMPs shall be incorporated into design. BMPs shall be incorporated such that runoff volume from 85 percent of average annual rainfall at a development site is pre-treated prior to its discharge from that site, or a pre-treated volume in compliance with RWQCB policy in effect at the time of design. Non-structural BMPs may include and are not limited to good housekeeping and other source control measures, such as the following: • Stencil catch basins and inlets to inform the public they are connected to the Bay; • Sweep streets on a regular schedule; • Use and dispose of paints, solvents, pesticides, and other chemicals properly; • Keep debris bins covered; and • Clean storm drain catch basins and properly dispose of sediment. Structural BMPs may include and are not limited to the following: • Minimize impervious areas directly connected to storm sewers; • Include drainage system elements in design as appropriate such as: o infiltration basins o detention/retention basins o vegetated swales (biofilters) O curb/drop inlet protection.	Prior to issuance of building permit (or other construction-related permit).	City/Port	7SGSW 7SGSE FITS	Applies to design phase only. No anticipated increases in storm water runoff flow for the FITS, 7SGSE or 7SGSW Projects because the Project improvements would have a net decrease of impervious surface. (FITS WQR, June 2018; 7SGSE AQR, May 2018; 7SGSW, May 2018).
6. Would the project otherwise substantially	Mitigation 4.14-1: Installation of groundwater extraction wells into the shallow water-bearing zone or Merritt Sand aquifer for any purpose other than	Prior to issuance of building	City/Port	N/A	For the 7SGSW Project, soil disturbance activities may

7SGSW, 7SGSE, FITS

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monito		GoPort Project	Notes (2018 GoPort Technical Studies References to Mitigation Measures)
degrade water quality? Would the project cause saltwater to intrude into shallow groundwater, cause contaminants to migrate to uncontaminated groundwater, or lead to degradation of surface water quality?	construction de-watering and remediation, including monitoring, shall be prohibited. Implementation of this measure would prevent saltwater from being drawn into the aquifer and potentially causing fresh water to become brackish or saline. Limiting extraction of shallow groundwater and groundwater from the Merritt Sand unit will prevent potential impacts to existing study area groundwater resources.	permit (or other construction-related permit); and during operations.			cause contaminated water to discharge off-site and into the San Francisco Bay. Mitigation 4.14-1 applies. For 7SGSE, temporary impacts to water quality during construction can be avoided or minimized by implementing temporary construction-site BMPs. The new roadway would be supported by a sealed slab to prevent groundwater intrusion; therefore, no permanent impacts to groundwater are anticipated. Long-term measures to address impacts to water resources are not expected. For FITS, The Project does not anticipate long-term dewatering, and the Project would have minimal grading and no added impervious area. Therefore, long-term impacts to groundwater are not anticipated.
	Mitigation 4.14-2: Extraction of groundwater for construction de-watering or remediation, including monitoring, shall be minimized where practicable; if extraction will penetrate into the deeper aquifers, than a study shall be conducted to determine whether contaminants of concern could migrate into the aquifer; if so, extraction shall be prohibited in that location. Implementation of this measure would prevent unnecessary extraction of groundwater and prohibit its extraction where contaminants of concern could migrate into deeper aquifers; therefore it will help avoid or reduce the potential migration of contaminants. The City and Port shall ensure that groundwater extraction, other than for remediation or construction dewatering, is minimized where practicable in the redevelopment project area.	Prior to issuance of building permit (or other construction-related permit); and during operations.	City/Port	7SGSW 7SGSE FITS	
	Mitigation 4.15-6: Site-specific design and best management practices shall be implemented to prevent runoff of recycled water to receiving waters.	Prior to issuance of building	City/Port	7SGSW 7SGSE	May apply if landscaping plans include the use of irrigation.

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE 7SGSW and FITS 7SGSE and FITS 7SGSW 7SGSE

Environmental Impact	Standard Conditions of Approval/Mitigation Measures		Mitigation Implementation/ Monitoring:		Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvar/Wingation Weasures	Schedule	Responsibility	Project	References to Mitigation Measures)
	Design of subsequent redevelopment activities shall ensure recycled water does not leave the site and enter receiving waters. Best management practices shall be implemented to prevent runoff of recycled water. These BMPs may be either structural or non-structural in nature and may include but are not limited to the following: • Preventing recycled water from escaping designated use areas through the use of: • berms • detention/retention basins • vegetated swales (biofilters) • Not allowing recycled water to be applied to irrigation areas when soils are saturated. • Plumbing portions of irrigation systems adjacent to receiving waters with potable water.	permit (or other construction-related permit).			
7. Would the project place housing, structures within a 100-year flood hazard area, as mapped on a federal Flood Hazard Boundary or Flood Insurance Rate Map or other flood hazard delineation map that would impede or redirect flood flows; or would the project expose people or structures to a substantial risk of loss, injury or death involving flooding?	Recommended Measure (not required by CEQA): The Project Sponsor should prepare a Sea Level Rise Adaptation Plan for City of Oakland for review and approval.	Prior to approval of PUD.	City/Port		
8. Would the project substantially alter the existing drainage pattern of the site or area, including through the alteration of the course, or increasing the rate or amount of	See above for Mitigation Measure 4.15-5, SCA HYD-1 through SCA HYD-3 a section)	and SCA GEO-1 (G	Geology and Soils		

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring:		GoPort	Notes (2018 GoPort Technical Studies
Environmental impact	Standard Conditions of Approvarivingation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
flow, of a creek, river or stream in a manner that would result in substantial erosion, siltation, or flooding, both on- or off-site?					
Noise					
1. Would the project generate noise in violation of the City of Oakland Noise Ordinance (Oakland Planning Code section 17.120.050) regarding construction noise, except if an acoustical analysis is performed that identifies recommend measures to reduce potential impacts?	 SCA NOI-1: Days/Hours of Construction Operation: The project applicant shall require construction contractors to limit standard construction activities as follows: a) Construction activities are limited to between 7:00 a.m. and 7:00 p.m. Monday through Saturday, except that barging and unloading of soil shall be allowed 24 hours per day, 7 days per week for about 15 months. b) Any construction activity proposed to occur outside of the standard hours of 7:00 a.m. to 7:00 p.m. Monday through Saturday for special activities (such as concrete pouring which may require more continuous amounts of time) shall be evaluated on a case by case basis, with criteria including the proximity of residential uses and a consideration of resident's preferences for whether the activity is acceptable if the overall duration of construction is shortened and such construction activities shall only be allowed with the prior written authorization of the Building Services Division. The project applicant shall also submit an air quality report prepared by a qualified professional evaluating the air quality impacts of the special activities, if the duration of each activity exceeds 6 months. c) No construction activity shall take place on Sundays or Federal holidays, except as noted above. d) Construction activities include but are not limited to: truck idling, moving equipment (including trucks, elevators, etc) or materials, deliveries, and construction meetings held on-site in a non-enclosed area. e) Applicant shall use temporary power poles instead of generators where feasible. 	Ongoing throughout demolition, grading, and/or construction.	City/Port	7SGSW 7SGSE FITS	7SGSE Project would exceed the City's construction noise thresholds of 65 dBA (hourly L _{eq}) at one receptor location (Pine and Gross Streets). Daytime construction noise for the 7SGSW Project would not exceed the City's construction noise thresholds of 65 dBA (hourly L _{eq}).
	SCA NOI-2: Noise Control: To reduce noise impacts due to construction, the project applicant shall require construction contractors to implement a site-specific noise reduction program, subject to the Planning and Zoning Division and the Building Services Division review and approval, which includes the following measures:	Ongoing throughout demolition, grading, and/or construction.	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. 7SGSE Project would exceed the City's construction noise thresholds of 65 dBA (hourly Leq)

Engineer and I I I I I I I I I I I I I I I I I I I		Chandand Candidians of American Marking Market	Mitigation Im Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	ental Impact Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)	
	a)	Equipment and trucks used for project construction shall utilize the best available noise control techniques (e.g., improved mufflers, equipment redesign, use of intake silencers, ducts, engine enclosures and acoustically-attenuating shields or shrouds, wherever feasible).				at one receptor location (Pine and Gross Streets).
	b)	Except as provided herein, Impact tools (e.g., jack hammers, pavement breakers, and rock drills) used for project construction shall be hydraulically or electrically powered to avoid noise associated with compressed air exhaust from pneumatically powered tools. However, where use of pneumatic tools is unavoidable, an exhaust muffler on the compressed air exhaust shall be used; this muffler can lower noise levels from the exhaust by up to about 10 dBA. External jackets on the tools themselves shall be used, if such jackets are commercially available_and this could achieve a reduction of 5 dBA. Quieter procedures shall be used, such as drills rather than impact equipment, whenever such procedures are available and consistent with construction procedures.				Daytime construction noise for the 7SGSW Project would not exceed the City's construction noise thresholds of 65 dBA (hourly $L_{\rm eq}$).
	c)	Stationary noise sources shall be located as far from adjacent receptors as possible, and they shall be muffled and enclosed within temporary sheds, incorporate insulation barriers, or use other measures as determined by the City to provide equivalent noise reduction.				
	d)	The noisiest phases of construction shall be limited to less than 10 days at a time. Exceptions may be allowed if the City determines an extension is necessary and all available noise reduction controls are implemented.				
	bui pro me	A NOI-3: Noise Complaint Procedures: Prior to the issuance of each lding permit, along with the submission of construction documents, the ject applicant shall submit to the Building Services Division a list of asures to respond to and track complaints pertaining to construction noise. see measures shall include:	Ongoing throughout demolition, grading, and/or construction.	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. Conduct ambient noise testing prior to construction for 7SGSW and 7SGSE Projects.
	a)	A procedure and phone numbers for notifying the Building Services Division staff and Oakland Police Department; (during regular construction hours and off-hours);				
	b)	A sign posted on-site pertaining with permitted construction days and hours and complaint procedures and who to notify in the event of a problem. The sign shall also include a listing of both the City and construction contractor's telephone numbers (during regular construction hours and off-hours);				
	c)	The designation of an on-site construction complaint and enforcement manager for the project;				

Environmental Import	ental Impact Standard Conditions of Approval/Mitigation Measures -	Mitigation Im Monit	-	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mugation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	 d) Notification of neighbors and occupants within 300 feet of the project construction area at least 30 days in advance of extreme noise generating activities about the estimated duration of the activity; and e) A preconstruction meeting shall be held with the job inspectors and the general contractor/on-site project manager to confirm that noise measures and practices (including construction hours, neighborhood notification, posted signs, etc.) are completed. 				
	SCA NOI-6: Pile Driving and Other Extreme Noise Generators: To further reduce potential pier drilling, pile driving and/or other extreme noise generating construction impacts greater than 90dBA, a set of site-specific noise attenuation measures shall be completed under the supervision of a qualified acoustical consultant. Prior to commencing construction, a plan for such measures shall be submitted for review and approval by the Planning and Zoning Division and the Building Services Division to ensure that maximum feasible noise attenuation will be achieved. This plan shall be based on the final design of the project. A third-party peer review, paid for by the project applicant, may be required to assist the City in evaluating the feasibility and effectiveness of the noise reduction plan submitted by the project applicant. The criterion for approving the plan shall be a determination that maximum feasible noise attenuation will be achieved. A special inspection deposit is required to ensure compliance with the noise reduction plan. The amount of the deposit shall be determined by the Building Official, and the deposit shall be submitted by the project applicant concurrent with submittal of the noise reduction plan. The noise reduction plan shall include, but not be limited to, an evaluation of implementing the following measures. These attenuation measures shall include as many of the following control strategies as applicable to the site and construction activity: a) Erect temporary plywood noise barriers around the construction site, particularly along on sites adjacent to residential buildings; b) Implement "quiet" pile driving technology (such as pre-drilling of piles, the use of more than one pile driver to shorten the total pile driving duration), where feasible, in consideration of geotechnical and structural requirements and conditions; c) Utilize noise control blankets on the building structure as the building is erected to reduce noise emission from the site;	Ongoing throughout demolition, grading, and/or construction.	City/Port	7SGSW 7SGSE	Applies to Contractor. 7SGSE Project would exceed the City's construction noise thresholds of 65 dBA (hourly Leq) at one receptor location (Pine and Goss Streets). Daytime construction noise for the 7SGSW Project would not exceed the City's construction noise thresholds of 65 dBA (hourly Leq).

Environmental Impact	Standard Conditions of Approval/Mitigation Measures		Mitigation Implementation/ Monitoring:		Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approva/Mingation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	of sound blankets for example and implement such measure if such measures are feasible and would noticeably reduce noise impacts; and				
	e) Monitor the effectiveness of noise attenuation measures by taking noise measurements.				
2. Would the project generate noise in violation of the City of Oakland nuisance standards (Oakland Municipal Code section 8.18.020) regarding persistent construction-related noise?	See above for SCA NOI-1, SCA NOI-2, SCA NOI-3, and SCA NOI-6				
3. Would the project generate noise in violation of the City of Oakland Noise Ordinance (Oakland Planning Code section 17.120.050) regarding operational noise?	SCA NOI-4: Interior Noise: If necessary to comply with the interior noise requirements of the City of Oakland's General Plan Noise Element and achieve an acceptable interior noise level, noise reduction in the form of sound-rated assemblies (i.e., windows, exterior doors, and walls), and/or other appropriate features/measures, shall be incorporated into project building design, based upon recommendations of a qualified acoustical engineer and submitted to the Building Services Division for review and approval prior to issuance of building permit. Final recommendations for sound-rated assemblies, and/or other appropriate features/measures, will depend on the specific building designs and layout of buildings on the site and shall be determined during the design phases. Written confirmation by the acoustical consultant, HVAC or HERS specialist, shall be submitted for City review and approval, prior to Certificate of Occupancy (or equivalent) that:	Prior to issuance of a building permit and Certificate of Occupancy.	City/Port	N/A	There is no operational noise increases from the 7SGSW or 7SGSE Projects. Noise impacts not applicable to FITS Project.
	a) Quality control was exercised during construction to ensure all air-gaps and penetrations of the building shell are controlled and sealed; and				
	b) Demonstrates compliance with interior noise standards based upon performance testing of a sample unit.				
	c) Inclusion of a Statement of Disclosure Notice in the CC&R's on the lease or title to all new tenants or owners of the units acknowledging the noise generating activity and the single event noise occurrences. Potential features/measures to reduce interior noise could include, but are not limited to, the following:				

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring:	GoPort	Notes (2018 GoPort Technical Studies	
Environmental impact	Standard Conditions of Approvar/Wingation Weasures	Schedule	Responsibility	Project	References to Mitigation Measures)
	 i) Installation of an alternative form of ventilation in all units identified in the acoustical analysis as not being able to meet the interior noise requirements due to adjacency to a noise generating activity, filtration of ambient make-up air in each unit and analysis of ventilation noise if ventilation is included in the recommendations by the acoustical analysis. ii) Prohibition of Z-duct construction. 				
	SCA NOI-5: Operational Noise-General: Noise levels from the activity, property, or any mechanical equipment on site shall comply with the performance standards of Section 17.120 of the Oakland Planning Code and Section 8.18 of the Oakland Municipal Code. If noise levels exceed these standards, the activity causing the noise shall be abated until appropriate noise reduction measures have been installed and compliance verified by the Planning and Zoning Division and Building Services.	Ongoing	City/Port	N/A	There is no operational noise increases from the 7SGSW or 7SGSE Projects. Noise impacts not applicable to FITS Project.
4. Would the project generate noise resulting in a 5 dBA permanent increase in ambient noise levels in the project vicinity above levels existing without the project; or, if under a cumulative scenario where the cumulative increase results in a 5 dBA permanent increase in ambient noise levels in the project vicinity without the project (i.e., the cumulative condition including the project compared to the existing conditions) and a 3 dBA permanent increase is attributable to the project (i.e., the cumulative condition including the project compared to the cumulative condition including the project compared to the	See above for SCA NOI-4 and NOI-5				

7SGSW, 7SGSE, FITS 7SGSW

7SGSW and 7SGSE

7SGSW and FITS

7SGSE and FITS

FITS

7SGSW

7SGSE

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit		GoPort	Notes (2018 GoPort Technical Studies
Environmental impact	Standard Conditions of Approval/Midgation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
cumulative baseline condition without the project)?					
5. Would the project be exposed to a community noise in conflict with the land use compatibility guidelines of the Oakland General Plan after incorporation of all applicable Standard Conditions of Approval?	See above for SCA NOI-4 and NOI-5				
6. Would the project expose persons to or generate noise levels in excess of applicable standards established by a regulatory agency (e.g., occupational noise standards of OSHA)?	See above for SCA NOI-5				
7. Would the project, during either project construction or project operation, expose persons to or generate groundborne vibration that exceeds the criteria established by the Federal Transit Administration (FTA)?	See above for SCA NOI-1, SCA NOI-2, SCA NOI-3, and SCA NOI-6				
Public Outreach					
	Mitigation PO-1 (Stakeholder Review of Air Quality and Trucking Plans): The City of Oakland ("City") and Prologis CCIG Oakland Global, LLC ("Developer") shall engage the public in the development of the following plans required by the SCA/MMRP related to potential air quality and trucking impacts	Ongoing; as stated	City and Port and individual projects	N/A	Only applies to the Prologis and CCIG projects.

7SGSW, 7SGSE, FITS

7SGSW and 7SGSE

7SGSW and FITS

7SGSE and FITS

FITS

7SGSW

7SGSE

Environmental Impact	Standard Conditions of Approval/Mitigation Measures		Mitigation Implementation/ Monitoring:		Notes (2018 GoPort Technical Studies
Environmental impact	Standard Conditions of Approvar/windgation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	on the surrounding area during construction and operation of the project (the "Subject Plans"): SCA AIR-1 (Construction Management Plan) SCA AIR-2 (Construction-Related Air Pollution Controls) Mitigation 4.3-7 (Truck Management Plan) Mitigation 4.4-3b (Maritime and Rail-Related Emissions Reduction Plan) Mitigation 4.4-5 (Transportation Control Measures) Mitigation 4.4-6 (Energy-Conserving Fixtures and Designs) Mitigation 5.4-1 (Demonstration Projects) SCA TRANS-1 (Parking and Transportation Demand Management) SCA TRANS-2 (Construction Traffic and Parking) Mitigation 4.3-13 (Traffic Control Plan – Hazardous Materials) A. Stakeholder List. The City shall maintain a list of the names and electronic mail addresses of the stakeholders that have expressed an interest in receiving information on the Subject Plans (the "Stakeholder List"). The Stakeholder List shall include the recipients of the July 3, 2013, letter related to the Construction Management Plan for the Public Improvements (which included SCA AIR-1, SCA AIR-2, SCA TRANS-2, MM 4.3-13 and SCA 4.4-6) and such additional stakeholders that submit a written request to the City to be added to the Stakeholder List. D. Quarterly Meetings. Beginning in September of 2013 and continuing until such time as the City Administrator has approved all of the Subject Plans, the City and the Developer shall jointly host quarterly meetings to discuss the status of the Subject Plans. The City and the Developer shall make a good faith effort to schedule the meeting				

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE

7SGSW and FITS

7SGSE and FITS

FITS

7SGSW

7SGSE

Environmental Impact	Standard Conditions of Approval/Mitigation Massaures	Mitigation Imp Monite	=	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	AIR-2, SCA TRANS-2, MM 4.3-13 and SCA 4.4-6 with respect to vertical improvements will be subject to this item (c). d. Public Review and Comment Period. Prior to approving any draft Subject Plan, the City shall provide the parties included in the Stakeholder List with seventeen (17) calendar days within which to review and provide written comments to any draft Subject Plan, and such written comments must be received by the City no later than 5:00 p.m. on the seventeenth day; provided, however, if the seventeen (17) day period expires on any day other a business day, the expiration date shall be extended to 5:00 p.m. on the next business day. The seventeen (17) day period shall be initiated by the City's electronic mail to the parties included in the Stakeholder List. During the 17-day public review and comment period the City shall make the draft Subject Plan available for public review such as posting the document on the City's website. e. Informational Council Presentation. City staff shall provide the City Council with an informational presentation of each approved Subject Plan within ninety				
Public Services	(90) calendar days after the City Administrator's approval of such Subject Plan. Such presentation shall include a summary of the public outreach implemented pursuant to this mitigation measure and the requirements and goals of the applicable approved Subject Plan.				
1. Would the project result in increased demand for fire protection services and first responder medical emergency services?	SCA PSU-1: Underground Utilities: The project applicant shall submit plans for review and approval by the Building Services Division and the Public Works Agency, and other relevant agencies as appropriate that show all fire alarm conduits and similar facilities placed underground. The new facilities shall be placed underground along the project applicant's street frontage and from the project applicant's structures to the point of service. The plans shall show all fire water service and fire alarm facilities installed in accordance with standard specifications of the serving utilities.	Prior to issuance of a building permit.	City/Port	7SGSE FITS	Applies to design phase only.
	SCA PSU-2: Fire Safety Phasing Plan: The project applicant shall submit a separate fire safety phasing plan to the Planning and Zoning Division and Fire Services Division for their review and approval. The fire safety plan shall include all of the fire safety features incorporated into the project and the schedule for implementation of the features. Fire Services Division may require changes to the plan or may reject the plan if it does not adequately address fire hazards associated with the project as a whole or the individual phase.	Prior to issuance of a demolition, grading, and/or construction and concurrent with any p-job submittal .permit.	City/Port	7SGSW 7SGSE	
	Mitigation 4.9-1. The City and Port shall cooperatively investigate the need for, and if required shall fund on a fair-share basis, development and operation of	Pre-operations; at time Port and	City and Port	N/A	GoPort projects would not increase the demand for emergency or fire services.

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Imp Monite	=	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvar/Wingation Weasures	Schedule	Responsibility	Project	References to Mitigation Measures)
	increased firefighting and medical emergency response services via fireboat to serve the OARB sub-district. The City and Port of Oakland will each contribute a fair share toward cooperatively investigating the need for increased firefighting and emergency response services to serve the redevelopment area west of I-880. This investigation shall include consultation with the OES and OFD. Should this investigation conclude, based on detailed redevelopment design, that increased fireboat services are required, the Port and the City shall each fund its fair share to equip and staff fireboat-based services in the OARB sub-district. In addition, as subsequent redevelopment activities occur, the City and Port shall be allowed to develop fee formulae (to recoup initial investment from future development or tenants), as well as a long-term cost-sharing formula (to equitably distribute the cost of continuing operations). The fire facility will be constructed after basic underground infrastructure is	Gateway development area employees exceed 2,044 (1995 baseline)			
	constructed, and before any people-attracting subsequent redevelopment activities begin operations. Mitigation 4.9-2: The Port and City shall work with OES to ensure changes in local area circulation are reflected in the revised Response Concept. The Port and City would provide information to the OES to facilitate that agency's accurate revision of its Response Concept and Annex H. In particular,	Pre-construction	City/Port	N/A	GoPort projects would not increase the demand for emergency or fire services.
	the City and Port would provide OES information regarding new and proposed project area development, intensification and changes in land uses, realignment of area roadways, and construction of new local circulation facilities.				
	Mitigation 4.9-3: The Port and City shall require developers within their respective jurisdictions to notify OES of their plans in advance of construction or remediation activities. Each developer proposing construction in the redevelopment project area would be required to notify OES prior to initiation of construction, so that OES may plan emergency access and egress taking into consideration possible conflicts or interference during the construction phase. The developer would also be required to notify OES once construction is complete.	Pre-construction	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. All projects to provide standard notification.
Traffic and Transportation	n				

T		Mitigation Im Monit		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
Project Impacts 1. At a study, signalized intersection which is located outside the Downtown area, would the Project cause the level of service (LOS) to degrade to worse than LOS D (i.e., LOS E)?	 Mitigation Measure 3.16-1: 7th Street & I-880 Northbound Off-Ramp (#12)⁴. The project sponsor shall fund, prepare, and install the approved plans and improvements: Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the PM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit the following to City of Oakland's Transportation Engineering Division and Caltrans for review and approval: Plans, Specifications, and Estimates (PS&E) to modify the intersection. All elements shall be designed to City standards in effect at the time of construction and all new or upgraded signals should include these enhancements. All other facilities supporting vehicle travel and alternative modes through the intersection should be brought up to both City standards and ADA standards (according to Federal and State Access Board guidelines) at the time of construction. Current City Standards call for the elements listed below: 2070L Type Controller GPS communication (clock) Accessible pedestrian crosswalks according to Federal and State Access Board guidelines City Standard ADA wheelchair ramps Full actuation (video detection, pedestrian push buttons, bicycle detection) Accessible Pedestrian Signals, audible and tactile according to Federal Access Board guidelines Countdown Pedestrian Signals Signal interconnect and communication to City Traffic Management Center for corridors identified in the City's ITS Master Plan for a maximum of 600 feet Signal timing plans for the signals in the coordination group. 	At issuance of first Certificate of Occupancy (CO)	City/Port	N/A	Level of Service (LOS) at 7 th Street/I-880 Northbound Off- ramp would remain at LOS D for both the No-Build and Build Alternative. (GoPort TSR, April 2018).
	Mitigation Measure 3.16-2: San Pablo Ave & Ashby Avenue (#42). To implement this measure, the Project Sponsor shall coordinate with City of	At issuance of first Certificate	City/Port	N/A	Outside of GoPort Project Area.

⁴ The numbers appearing after the location of the intersection listed refer to Figure 3.16-1 in the IS/Addendum that illustrates the study intersections.

7SGSW, 7SGSE, FITS

Environmental Import	Standard Conditions of Annuaral/Mitigation Magazines	Mitigation Im Monit		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	Berkeley and Caltrans, and shall fund, prepare, and install the improvements consistent with City of Berkeley and/or Caltrans standards.	of Occupancy (CO)			
	 Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the PM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. 				
2. At two intersections, the project would cause (a) the total intersection average vehicle delay to increase by two (2) or more seconds, or (b) an	Mitigation Measure 3.16-3: 7^{th} <i>Street & Harrison Street (#18).</i> To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval.	At issuance of first Certificate of Occupancy (CO)	City/Port	N/A	Outside of GoPort Project Area.
increase in average delay for any of the critical movements of four (4) seconds or	 Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the PM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. 				
more; or (c) the volume-to-capacity ("V/C") ratio exceeds	The project sponsor shall fund, prepare, and install the approved plans and improvements.				
0.03 or more (but only if the delay values are greater than 120 seconds of average intersection delay as delay values over 120	Mitigation Measure 3.16-4: <i>12th Street & Castro Street</i> (#29). To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval.	At issuance of first Certificate of Occupancy (CO)	City/Port	N/A	Outside of GoPort Project Area.
seconds tend to increase exponentially and are then generally considered unreliable).	 Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the PM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. 				
	The project sponsor shall fund, prepare, and install the approved plans and improvements.				
3. Redevelopment would cause some roadway segments on the Congestion Management Program (CMP) to a) degrade to LOS F; or b) increase the V/C ratio by more	 SCA TRANS-1: Parking and Transportation Demand Management: The project sponsor shall pay for and submit for review and approval by the City a Transportation Demand Management (TDM) plan containing strategies to: Reduce the amount of traffic generated by new development and the expansion of existing development, pursuant to the City's police power and necessary in order to protect the public health, safety and welfare. 	For construction: Prior to issuance of first permit related to construction (e.g.,	City/Port	N/A	Only one intersection, Maritime Street and West Grand Avenue would degrade to LOS F, in both the 2040 No-Build and Build Alternative. Therefore, the decrease in LOS would occur with or without the GoPort project.
than three percent for a roadway segment that					

Environmental Impact		Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring:		GoPort	Notes (2018 GoPort Technical Studies		
Environmental Impact	act		Schedule	Responsibility	Project	References to Mitigation Measures)		
would operate at LOS F without the project.	2.	Ensure that expected increases in traffic resulting from growth in employment and housing opportunities in the City of Oakland will be adequately mitigated.	demolition, grading, etc.) For operation:					
	3.	Reduce drive-alone commute trips during peak traffic periods by using a combination of services, incentives, and facilities.	Prior to issuance of a final					
	4.	Promote more efficient use of existing transportation facilities and ensure that new developments are designed in ways to maximize the potential for alternative transportation usage.	building permit and on-going related to submission of					
	5.	Establish an ongoing monitoring and enforcement program to ensure that the desired alternative mode use percentages are achieved.	Parking and TDM Plan annual					
	sha	e project sponsor shall implement the approved TDM plan. The TDM plan ll include strategies to increase pedestrian, bicycle, transit, and pool/vanpool use. All four modes of travel shall be considered, and parking nagement and parking reduction strategies should be included.	compliance report					
	Act	ions to consider include the following:						
	a)	Inclusion of additional long term and short term bicycle parking that meets the design standards set forth in chapter five of the Bicycle Master Plan, and Bicycle Parking Ordinance, and shower and locker facilities in commercial developments that exceed the requirement.						
	b)	Construction of and/or access to bikeways per the Bicycle Master Plan; construction of priority bikeways, onsite signage and bike lane striping.						
	c)	Installation of safety elements per the Pedestrian Master Plan (such as cross walk striping, curb ramps, count down signals, bulb outs, etc.) to encourage convenient and safe crossing at arterials.						
	d)	Installation of amenities such as lighting, street trees, trash receptacles per the Pedestrian Master Plan and any applicable streetscape plan.						
	e)	Construction and development of transit stops/shelters, pedestrian access, way finding signage, and lighting around transit stops per transit agency plans or negotiated improvements.						
	f)	Direct onsite sales of transit passes purchased and sold at a bulk group rate (through programs such as AC Transit Easy Pass or a similar program through another transit agency).						
	g)	Employees or residents can be provided with a subsidy, determined by the project sponsor and subject to review by the City, if the employees or residents use transit or commute by other alternative modes.						
	h)	Provision of ongoing contribution to AC Transit service to the area between the development and nearest mass transit station. If that is not available, an						

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE 7SGSW and FITS 7SGSW 7SGSE 7SGSW 7SGSE

Environmental Impact		Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit	=	GoPort	Notes (2018 GoPort Technical Studies
Environmental impact		Standard Conditions of Approva/Midgation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
		ongoing contribution to an existing area shuttle service between the development and nearest mass transit station. The last option is establishment of a new shuttle service between the development and nearest mass transit station may be developed. The contribution required for the service (any option) will be based on the cost of the last option.				
	i)	Guaranteed ride home program for employees, either through 511.org or through separate program.				
	j)	Pre-tax commuter benefits (commuter checks) for employees.				
	k)	Free designated parking spaces for on-site car-sharing program (such as City Car Share, Zip Car, etc.) and/or car-share membership for employees or tenants.				
	1)	On-site carpooling and/or vanpool program that includes preferential (discounted or free) parking for carpools and vanpools.				
	m)	Distribution of information concerning alternative transportation options.				
	n)	Parking spaces sold/leased separately for residential units. Charge employees for parking, or provide a cash incentive or transit pass alternative to a free parking space in commercial properties.				
	0)	Parking management strategies; including attendant/valet parking and shared parking spaces.				
	p)	Requiring tenants to provide opportunities and the ability to work off-site.				
	q)	Allow employees or residents to adjust their work schedule in order to complete the basic work requirement of five eight-hour workdays by adjusting their schedule to reduce vehicle trips to the worksite.				
	r)	Provide or require tenants to provide employees with staggered work hours involving a shift in the set work hours of all employees at the workplace or flexible work hours involving individually determined work hours.				
	appreventim state staff and may sha income	e project sponsor shall submit an annual compliance report for review and proval by the City. This report will be reviewed either by City staff (or a peer iew consultant, chosen by the City and paid for by the project sponsor). If ely reports are not submitted, the reports indicate a failure to achieve the red policy goals, or the required alternative mode split is still not achieved, if will work with the project sponsor to find ways to meet their commitments a achieve trip reduction goals. If the issues cannot be resolved, the matter by be referred to the Planning Commission for resolution. Project sponsors ll be required, as a condition of approval, to reimburse the City for costs surred in maintaining and enforcing the trip reduction program for the proved project.				

7SGSW, 7SGSE, FITS

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Imp Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approva/Midgation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
4. The project would directly or indirectly cause or expose roadway users to a permanent and substantial transportation hazard due to a new or existing physical design feature or incompatible uses?	Mitigation 4.3-5: Redevelopment elements shall be designed in accordance with standard design practice and shall be subject to review and approval of the City or Port design engineer. Through design review, the City and/or Port, as applicable, shall ensure the design of roadways, bicycle and pedestrian facilities, parking lots, and other transportation features comply with design standards and disallow design proposals that likely to result in traffic hazards. Any mitigation or redevelopment features that may directly affect Caltrans facilities shall be submitted for review by that agency.	Prior to approval of PUD.	City/Port	7SGSW 7SGSE FITS	Applies to design phase only.
	 Mitigation 4.3-7: The City and the Port shall continue and shall work together to create a truck management plan designed to reduce the effects of transport trucks on local streets. The City and Port shall fund on a fair share basis, implementation of this plan. The truck management plan may include, and is not limited to, the following elements: Analyze truck traffic in West Oakland; Traffic calming strategies on streets not designated as truck routes designed to discourage truck through travel; Truck driver education programs; Expanded signage, including truck prohibitions on streets not designated as truck routes; Traffic signal timing improvements; Explore the feasibility of truck access to Frontage Road; Roadway and terminal gate design elements to prevent truck queues from impeding the flow of traffic on public streets; and Continue Port funding of two police officers to enforce truck traffic prohibitions on local streets. 	Prior to issuance of a final building permit	City and Port	N/A	
	Mitigation 4.3-8: Provide an emergency service program and emergency evacuation plan using waterborne vessels. The City shall provide emergency access to the OARB sub-district by vessel. The area is currently served by fire boat out of the Jack London Square Fire Station. The City may elect to equip that fire boat with first response medical emergency personnel as well as limited hazardous materials response personnel and equipment (see also Mitigation Measure 4.9-1). Major developers shall fund these improvements on a fair share basis.	Pre-operations; at time Port and Gateway development area employees exceed 2,044 (1995 baseline)	City/Port	N/A	Not applicable.

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Imp Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvar/Midgadon Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	With regard to Maritime Street between 7th Street and West Grand Avenue: Mitigation Measure 3.16-5: The City shall provide a shoulder with a minimum width of 8 feet on the west side of Maritime Street to accommodate queuing trucks and minimize intrusion onto the southbound travel lane. Mitigation Measure 3.16-6: The City shall provide a 9-foot wide area along the entire west side of Maritime Street in this area to accommodate a sidewalk and utilities; exact dimensions of these elements will be determined by the City's Transportation and Infrastructure Divisions during the PUD process. Mitigation Measure 3.16-7: The City shall provide an 18-foot wide area along the entire east side of Maritime Street in this area to accommodate a Class 1 bicycle path and utilities; exact dimensions of these elements will be determined by the City's Transportation and Infrastructure Divisions during the PUD process.	Prior to approval of the PUD	City/Port	7SGSW FITS	Applies to design phase only. Measures completed as part of the OAB; GoPort design must maintain the improvements.
	With regard to North Maritime (formerly Wake Avenue): Mitigation Measure 3.16-8: The City shall provide 2 travel lanes in each direction in this area with shoulders on each side for bicycle lanes. The exact dimensions of these elements will be determined by the City's Transportation and Infrastructure Divisions during the PUD process.	Prior to approval of the PUD	City/Port	N/A	Outside of GoPort Project Area.
	With regard to Burma Road between Maritime Street and West Oakland (Burma East): Mitigation Measure 3.16-9: The City shall provide a 9-foot wide area along the entire north side of Burma Street in this area to accommodate utilities and a sidewalk; bicycles will be accommodated on the shoulder; exact dimensions of these elements will be determined by the City's Transportation and Infrastructure Divisions during the PUD process.	Prior to approval of the PUD	City/Port	N/A	Outside of GoPort Project Area.
	Mitigation Measure 3.16-10: The City shall provide a 7-foot wide area along the entire south side of Burma Street in this area to accommodate utilities; bicycles will be accommodated on the shoulder; exact dimensions of these elements will be determined by the City's Transportation and Infrastructure Divisions during the PUD process.	Prior to approval of the PUD	City/Port	N/A	Outside of GoPort Project Area.
	With regard to Burma Road between Maritime Street and Railroad Tracks (Burma West):	Prior to approval of the PUD	City/Port	N/A	Outside of GoPort Project Area.

FITS

7SGSW

7SGSE

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Imp Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental impact	Standard Conditions of Approvar/Windgation Weasures	Schedule	Responsibility	Project	References to Mitigation Measures)
	Mitigation Measure 3.16-11 : The City shall provide a 9-foot wide area along the entire south side of Burma Street in this area to accommodate utilities and a sidewalk; bicycles will be accommodated on the shoulder; exact dimensions of these elements will be determined by the City's Transportation and Infrastructure Divisions during the PUD process.				
	Mitigation Measure 3.16-12 : The City shall provide a 20-foot wide area along the entire north side of Burma Street in this area to accommodate utilities and a Class 1 bicycle path; exact dimensions of these elements will be determined by the City's Transportation and Infrastructure Divisions during the PUD process.				
	With regard to Burma Road between Railroad Tracks and Gateway Park (Burma Far West): Mitigation Measure 3.16-13: The City shall provide an 8-foot wide area along the entire south side of Burma Street in this area to accommodate utilities and a sidewalk; bicycles will be accommodated on the shoulder with a Class 2 bicycle lane; exact dimensions of these elements will be determined by the City's Transportation and Infrastructure Divisions during the PUD process.	Prior to approval of the PUD	City/Port	N/A	Outside of GoPort Project Area.
	Mitigation Measure 3.16-14: The City shall provide a shoulder along the entire north side of Burma Street in this area to accommodate bicycles with a Class 2 bicycle lane; exact dimensions of these elements will be determined by the City's Transportation and Infrastructure Divisions during the PUD process.	Prior to approval of the PUD	City/Port	N/A	Outside of GoPort Project Area.
	With regard to Emergency Access: Mitigation Measure 3.16-15a: The Project Sponsor shall develop, in consultation and coordination with adjacent property owners, including EBMUD, an emergency response plan for the 2012 Army Base Project, which addresses emergency ingress/egress. Mitigation Measure 3.16-15b: The Project Sponsor shall include in the design of West Burma Road turn-outs and turn-arounds at the appropriate locations and dimensions as required by the Fire Department, in order to allow for appropriate ingress and egress of emergency vehicles.	For MM 3.15-15a: at the time of issuance of the first Certificate of Occupancy (CO); For MM 3.15-15b: prior to approval of the PUD	City/Port	N/A	Outside of GoPort Project Area.
	Mitigation 4.3-10 (Parking Demand Study): The number of parking spaces provided in the project area shall comply with City Code or Port requirements, and/or with recommendations of a developer funded parking demand analysis. Through project review, the City and/or Port shall ensure an adequate supply of parking spaces will be provided. Major redevelopment project area developers	Prior to issuance of demolition, grading, or building permit; or ongoing as	City/Port	N/A	For operations.

•					
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental impact		Schedule	Responsibility	Project	References to Mitigation Measures)
	shall fund on a fair share basis a project area-wide, or potentially a sub-area specific parking demand study that shall take into consideration the TDM programs and policies developed through the Standard Conditions of Approval and Mitigation and Monitoring Program.	specified in SCA ULT-2.			
5. Project would directly or indirectly result in a permanent substantial decrease in pedestrian safety.	See above for Mitigation Measures 4.3-5				
6. Project would directly or indirectly result in a permanent substantial decrease in bicyclist safety.	See above for Mitigation Measures 4.3-5 and new Mitigation Measures 3.16-	5 through 3.16-15a	and 3.16-15b		
7. Project would generate substantial multi-modal traffic traveling across at-grade railroad crossings that cause or	See above for Mitigation Measures 4.3-5 and 4.3-7				
expose roadway users to a permanent and substantial transportation hazard?	 SCA TRANS-3: Railroad Crossings: Any proposed new or relocated railroad crossing improvements must be coordinated with California Public Utility Commission (CPUC) and affected railroads and all necessary permits/approvals obtained, including a GO 88-B Request (Authorization to Alter Highway Rail Crossings), if applicable. Appropriate safety-related design features and measures should be incorporated, including without limitation: a) Installation of grade separations at crossings, i.e., physically separating roads and railroad tracks by constructing overpasses or underpasses. b) Improvements to warning devices at existing highway rail crossings that are impacted by project traffic. c) Installation of additional warning signage. d) Improvements to traffic signaling at intersections adjacent to crossings, e.g., signal preemption. e) Installation of median separation to prevent vehicles from driving around railroad crossing gates. f) Where soundwalls, landscaping, buildings, etc. would be installed near crossings, maintaining the visibility of warning devices and approaching trains. 	Action required prior to railroad crossing construction	City/Port	7SGSW 7SGSE	Applies to both design phase and contractor. The GoPort Project would reconstruct substandard infrastructure and alleviate road/rail chokepoint. Applies to 7SGSW and 7SGSE due to rail crossings.

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE 7SGSW and FITS 7SGSE and FITS FITS

ITS 7SGSW

7SGSE

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit	•	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approvar/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	 g) Prohibition of parking within 100 feet of the crossings to improve the visibility of warning devices and approaching trains. h) Construction of pull-out lanes for buses and vehicles transporting hazardous materials. i) Installation of vandal-resistant fencing or walls to limit the access of pedestrians onto the railroad right-of-way. j) Elimination of driveways near crossings. k) Increased enforcement of traffic laws at crossings. l) Rail safety awareness programs to educate the public about the hazards of 				
	highway-rail grade crossings. Mitigation Measure 3.16-16: a. Redesign the Engineers Road to intersect the EBMUD driveway at least 100 feet north of the at-grade rail crossing or configure an internal circulation plan that prohibits turns from Engineers Road onto Wake Avenue. b. Provide a high visibility crosswalk with pedestrian crossing signs at the pedestrian crossing just west of the rail crossing on West Burma Road. c. Paint "KEEP CLEAR" on West Burma Road for westbound vehicles at the Truck Services driveway. d. Unless approved otherwise by the California Public Utility Commission (CPUC), construct all rail crossings at a minimum street-crossing angle of 45 degrees consistent with Institute of Transportation Engineers recommendations, 90 degrees is preferred for cross-traffic safety.	At the time of issuance of the first Certificate of Occupancy (CO)	City/Port	N/A	Not applicable.
	The Project Sponsor shall negotiate with EBMUD in good faith to reach an agreement which reasonably limits train movements from unreasonably parking, stopping and/or blocking access to EBMUD's main gate to the MWWTP. Specifically, the Master Developer shall coordinate the timing of its use of the tracks to a schedule that reduces, to the maximum extent feasible, any potentially adverse impacts to EBMUD's main gate to the MWWTP. The Project Sponsor shall make reasonable good faith efforts to explore the feasibility of, and if determined feasible, obtain/secure alternate emergency vehicle access to the MWWTP that would not be impacted by	At the time of issuance of the first Certificate of Occupancy (CO)	City/Port	N/A	Not applicable.

Environmental Impact	Standard Conditions of Approval/Mitigation Massures	Mitigation Im Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	the 2012 Army Base rail traffic. The City shall coordinate its efforts with EBMUD.				
8. Project could fundamentally conflict	See above for Mitigation Measures 3.16-5 through 3.16-15a and 3.16-15b				
with adopted City policies, plans, or programs regarding public transit, bicycle, or pedestrian facilities adopted for the purpose of avoiding or mitigating an environmental effect.	Mitigation 4.3-9: Redevelopment plans shall conform to City of Oakland or Port development standards with facilities that support transportation alternatives to the single-occupant automobile. Facilities that support transportation alternatives to the single-occupant automobile may include, and are not limited to, bus turnouts, bicycle racks, on-site showers, on-site lockers, and pedestrian and bicycle ways.	Prior to issuance of first permit related to construction (e.g., demolition, grading, etc.)	City/Port	N/A	Operational. Not applicable.
9. Would the project result in a substantial, though temporary, adverse effect on the circulation system during construction of the project.	SCA TRANS-2: Construction Traffic and Parking: The project sponsor and construction contractor shall meet with appropriate City of Oakland agencies to determine traffic management strategies to reduce, to the maximum extent feasible, traffic congestion and the effects of parking demand by construction workers during construction of this project (see also SCA TRANS-1, especially "h") and other nearby projects that could be simultaneously under construction. The project sponsor shall develop a construction management plan. The plan shall be submitted to EBMUD, the Port, and Caltrans for their review and comment ten (10) business days before submittal to the City. The project sponsor shall consider in good faith such comments and revise the plan as appropriate. The revised plan shall be submitted for review and approval by the City's Planning and Zoning Division, the Building Services Division, and the Transportation Services Division. The plan shall include at least the following items and requirements:	Prior to the issuance of a demolition, grading or building permit	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. Mitigation should include traffic mitigation during construction for workers (i.e. shuttle for workers from BART).
	 A set of comprehensive traffic control measures, including scheduling of major truck trips and deliveries to avoid peak traffic hours, detour signs if required, lane closure procedures, signs, cones for drivers, and designated construction access routes. 				
	b) Notification procedures for adjacent project sponsors and public safety personnel regarding when major deliveries, detours, and lane closures will occur.				
	 c) Location of construction staging areas for materials, equipment, and vehicles at an approved location. d) A process for responding to, and tracking, complaints pertaining to construction activity, including identification of an onsite complaint manager. The manager shall determine the cause of the complaints and 				

Engineers del Immed		Can land Conditions of American Marking the Market	Mitigation Im Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact		Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
		shall take prompt action to correct the problem. Planning and Zoning shall be informed who the Manager is prior to the issuance of the first permit issued by Building Services.				
	e)	Provision for accommodation of pedestrian flow.				
	f)	Provision for parking management and spaces for all construction workers to ensure that construction workers do not park in on-street spaces (see also SCA TRANS-1, especially "h").				
	g)	Any damage to the street caused by heavy equipment, or as a result of this construction, shall be repaired, at the applicant's expense, within one week of the occurrence of the damage (or excessive wear), unless further damage/excessive wear may continue; in such case, repair shall occur prior to issuance of a final inspection of the building permit. All damage that is a threat to public health or safety shall be repaired immediately. The street shall be restored to its condition prior to the new construction as established by the City Building Inspector and/or photo documentation, at the applicant's expense, before the issuance of a Certificate of Occupancy.				
	h)	Any heavy equipment brought to the construction site shall be transported by truck, where feasible.				
	i)	No materials or equipment shall be stored on the traveled roadway at any time.				
	j)	Prior to construction, a portable toilet facility and a debris box shall be installed on the site, and properly maintained through project completion.				
	k)	All equipment shall be equipped with mufflers.				
	1)	Prior to the end of each work day during construction, the contractor or contractors shall pick up and properly dispose of all litter resulting from or related to the project, whether located on the property, within the public rights-of-way, or properties of adjacent or nearby neighbors.				
	mai imp inte	crifically, to further implement SCA TRANS-2, a traffic construction nagement analysis was performed which recommended certain provements to the Adeline/5 th and Adeline/3 rd Street and Adeline Street prsection, which is discussed under construction impacts of the Traffic and proportation section of the 2012 OARB Initial Study/Addendum.				
	was (TC	tigation 4.3-13: Prior to commencing hazardous materials or hazardous ste remediation, demolition, or construction activities, a Traffic Control Plan CP) shall be implemented to control peak hours trips to the extent feasible, are the safety on the street system and assure that transportation activities are tective of human health, safety, and the environment.	Prior to issuance of first permit related to construction (e.g.,	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. Applies to 7SGSW, 7SGSE and FITS Projects.

FITS

7SGSW

7SGSE

Environmental Import	Standard Conditions of Annuaval/Mitigation Massaures	Mitigation Implementation/ Monitoring:		Monitoring:	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)	
	Construction and remediation TCPs shall be designed and implemented to reduce to the maximum feasible extent traffic and safety impacts to regional and local roadways.	demolition, grading, etc.)				
	The TCP shall address items including but not limited to: truck routes, street closures, parking for workers and staff, access to the project area and land closures or parking restrictions that may require coordination with and/or approval by the City, the Port and/or Caltrans. The TCP shall be submitted to the City Traffic Engineering and Planning divisions or the Port, as appropriate, for review and approval prior to the issuance of any building, demolition or grading permits. The City and the Port shall coordinate their respective approvals to maximize the effectiveness of the TCP measures. DTSC would have ongoing authority under its Remedial Action Plan/Remedial Monitoring Plan oversight and the Hazardous Substances Account Act to regulate remediation transportation activities, which must be protective of human health, safety and the environment.					
	Remediation and demolition/construction traffic shall be restricted to designated truck routes within the City, and the TCP shall include a signage program for all truck routes serving the site during remediation or demolition/construction. A signage program details the location and type of truck route signs that would be installed during remediation and demolition/construction to direct trucks to and from the project area. Truck access points for entry and exit should be included in the TCP. In addition, as determined by City of Port staff, the developer shall be responsible for repairing any damage to the pavement that is caused by remediation or demolition/construction vehicles for restoring pavement to preconstruction conditions.					
	Remediation and demolition/construction-related trips will be restricted to daytime hours, unless expressly permitted by the City or the Port, and to the extent feasible, trips will be minimized during the a.m. and p.m. peak hours.					
	The TCP shall identify locations for construction/remediation staging. Remediation staging areas are anticipated to be located near construction areas, since remediation will be largely coordinated with redevelopment. In addition, the TCP shall identify and provide off-street parking for remediation and demolition/construction staff to the extent possible throughout all phases of redevelopment. If there is insufficient parking available within walking distance of the site for workers, the developer shall provide a shuttle bus or other appropriate system to transfer workers between the satellite parking areas and remediation or demolition/construction site.					
	The TCP shall also include measures to control dust, requirements to cover all loads to control odors, and provisions for emergency response procedures, health and safety driver education, and accident notification.					

FITS

7SGSW 7SGSE

		Mitigation Im	=		Notes
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	GoPort Project	(2018 GoPort Technical Studies References to Mitigation Measures)
Cumulative Impacts Year 2020 for 2012 OARB Project (Compared to Year 2025 for 2002 EIR Project) 1. Increased congestion at signalized intersections outside the Downtown area exceeding the cumulatively significant threshold. (Year 2020)	 Mitigation Measure 3.16-17: West Grand Avenue & I-880 Frontage Road (#2). Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the AM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements. 7th Street & I-880 Northbound Off-Ramp (#12). See above for Mitigation 3.1 	At the time of issuance of the first Certificate of Occupancy (CO)	City/Port	N/A	Outside of GoPort Project area.
2. One intersection located outside the downtown area, where the level of service is LOS E, the project would cause the total intersection average vehicle delay to increase by four (4) or more seconds, or degrade to worse than LOS E. (Year 2020)	Mitigation Measure 3.16-18: San Pablo Ave & Ashby Ave (#42). • Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the PM peak hour. • Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall coordinate with the City of Berkeley and Caltrans, and shall fund, prepare, and install the approved plans and improvements.	At the time of issuance of the first Certificate of Occupancy (CO)	City/Port	N/A	Outside of GoPort Project area.
3. One intersection with LOS F, where the project would cause (a) the total intersection average vehicle delay to increase by two (2) or more seconds, or (b) an increase in average delay for any of the critical movements of four (4) seconds or more; or (c) the volume-to-capacity ("V/C") ratio	12th Street and Castro Street (#29) - See above for Mitigation Measure 3.16-4.				

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monite		GoPort	Notes (2018 GoPort Technical Studies
Environmental impact		Schedule	Responsibility	Project	References to Mitigation Measures)
exceeds three (3) percent. (Year 2020)					
4. Four roadway segments of the Congestion Management Program (CMP) would a) degrade to LOS F; or b) increase the V/C ratio by more than three percent for a roadway segment that would operate at LOS F without the project (Year 2020).	See above for Mitigation Measure 4.3-4 and SCA TRANS-1.				
Cumulative Impacts for Year 2035 for 2012 OARB Project (Compared to Year 2025 for 2002 EIR Project) 1. Three intersections located outside the Downtown area, which the project would cause the level of service (LOS) to degrade to worse than LOS D. (Year 2035)	 Mitigation Measure 3.16-19: West Grand Avenue & Maritime Street (#1). Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the PM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements. 	Mitigation at this intersection may be required by Year 2028. Investigation of the need for this mitigation shall be studied in 2028 and every three years thereafter until 2035 or until the mitigation measure is implemented, whichever occurs first.	City/Port	7SGSW FITS	Applies to design phase only. Outside of 7SGSE Project area.
	Mitigation Measure: 7th Street & I-880 Northbound Off-Ramp (#12). See about	ove for Mitigation	Measure 3.16-1.		
	Mitigation Measure 3.16-20: 7th Street & Union Street (#15).	Mitigation at	City/Port	N/A	Outside of GoPort Project area.
	 Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the AM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. 	by Year 2032. Investigation of			

measure is

implemented,

78GSW, 78GSE, F1	78GSW and 78GSE 78GSW and F115 78GS	E and FIIS	F115	/5G5W	/SGSE N/A
Environmental Impact	Standard Conditions of Approval/Mitigation Measures		nplementation/ toring:	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Anagation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements.	2032 and every three years thereafter until 2035 or until the mitigation measure is implemented, whichever occurs first.			
1. At one intersection located within the Downtown area, the project would cause the LOS to degrade to worse than LOS E. (Year 2035)	 Mitigation Measure 3.16-21: West Grand Avenue & Northgate Avenue (#8). Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the AM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements. 	Mitigation at this intersection may be required by Year 2030. Investigation of the need for this mitigation shall be studied in 2030 and every three years thereafter until 2035 or until the mitigation measure is implemented, whichever occurs first.	City/Port	N/A	Outside of GoPort Project area.
3. At two intersections located outside the Downtown area where the level of service is LOS E, would the project cause the total intersection average vehicle delay to increase by four (4) or more seconds, or degrade to worse than LOS E (Year 2035)	 Mitigation Measure 3.16-22: 5th Street & Union Street / I-880 North Ramps (#21). Optimize signal timing (i.e., increase the traffic signal cycle length to 100 seconds and adjust the allocation of green time for each intersection approach) for the PM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. 	Mitigation at this intersection may be required by Year 2022. Investigation of the need for this mitigation shall be studied in 2022 and every three years thereafter until 2035 or until the mitigation	City/Port	N/A	Outside of GoPort Project area.

The project sponsor shall fund, prepare, and install the approved plans and

7SGSW, 7SGSE, FITS

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit		GoPort	Notes (2018 GoPort Technical Studies
Environmental impact		Schedule	Responsibility	Project	References to Mitigation Measures)
		whichever occurs first.			
	 Mitigation Measure 3.16-23: MacArthur Boulevard & Market Street (#33). Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the AM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements. 	Mitigation at this intersection may be required by Year 2032. Investigation of the need for this mitigation shall be studied in 2032 and every three years thereafter until 2035 or until the mitigation measure is implemented,	City/Port	N/A	Outside of GoPort Project area.
4. Eleven intersections where the level of service is LOS F, the project would cause (a) the total intersection average vehicle delay to increase by two (2) or more seconds, or (b) an increase in average delay for any of the critical movements of four (4) seconds or more; or (c) the volume-to-capacity ("V/C") ratio increases 0.03 or more (but only if the delay values are greater than 120 seconds of average	Mitigation Measure 3.16- 24: West Grand Avenue & I-880 Frontage Road (#2). • Optimize signal timing (i.e., increase the traffic signal cycle length and adjust the allocation of green time for each intersection approach) for the AM and PM peak hours. • Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements.	whichever occurs first. Mitigation at this intersection may be required by Year 2021. Investigation of the need for this mitigation shall be studied in 2021 and every three years thereafter until 2035 or until the mitigation measure is implemented, whichever occurs first.	City/Port	N/A	Outside of GoPort Project area.
intersection delay as delay values over 120 seconds tend to increase exponentially and are then generally considered unreliable). (Year 2035)	 Mitigation Measure 3.16- 25: West Grand Avenue & Adeline Street (#4). Optimize signal timing (i.e., increase the traffic signal cycle length to 90 seconds and adjust the allocation of green time for each intersection approach) for the PM peak hour. 	Mitigation at this intersection may be required by Year 2032. Investigation of the need for this	City/Port	N/A	Outside of GoPort Project area.

7SGSW, 7SGSE, FITS

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit	=	GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact		Schedule	Responsibility	Project	References to Mitigation Measures)
	 Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements. 	mitigation shall be studied in 2032 and every three years thereafter until 2035 or until the mitigation measure is implemented, whichever occurs first.			
	 Mitigation Measure 3.16- 26: West Grand Avenue & Market Street (#5) Provide split phasing for northbound and southbound movements. Optimize signal timing (i.e., increase the traffic signal cycle length to 120 seconds and adjust the allocation of green time for each intersection approach) for both the AM and PM peak hours. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements. 	Mitigation at this intersection may be required by Year 2022. Investigation of the need for this mitigation shall be studied in 2022 and every three years thereafter until 2035 or until the mitigation measure is implemented, whichever occurs first.	City/Port		
	 Mitigation Measure 3.16-27: West Grand Avenue & San Pablo Avenue (#6) Remove approximately seven (7) parking spaces on the south side of West Grand Avenue; add an eastbound through lane between San Pablo Avenue and Martin Luther King Jr. Way; and convert the eastbound right turn lane to a through-right combination lane. Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the PM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. 	Mitigation at this intersection may be required by Year 2026. Investigation of the need for this mitigation shall be studied in 2026 and every three years thereafter until 2035 or until the mitigation measure is implemented,	City/Port	N/A	Outside of GoPort Project area.

Engineer and I I was at	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monit		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact		Schedule	Responsibility	Project	References to Mitigation Measures)
	The project sponsor shall fund, prepare, and install the approved plans and improvements.	whichever occurs first.			
	 Mitigation Measure 3.16- 28: West Grand Avenue & Harrison Street (#9) Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the PM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements. 	Mitigation at this intersection may be required by Year 2025. Investigation of the need for this mitigation shall be studied in 2025 and every three years thereafter until 2035 or until the mitigation measure is implemented, whichever occurs first.	City/Port	N/A	Outside of GoPort Project area.
	 Mitigation Measure 3.16- 29: 7th Street & Harrison Street (#18) Optimize signal timing (i.e., increase the traffic signal cycle length to 80 seconds and adjust the allocation of green time for each intersection approach) for the PM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements. 	Mitigation at this intersection may be required at the time of Project construction. Investigation of the need for this mitigation shall be studied at the time of construction and every three years thereafter until 2035 or until the mitigation measure is implemented, whichever occurs first.	City/Port	N/A	Outside of GoPort Project area.
	Mitigation Measure 3.16- 30: 6th Street & Jackson Street (#20)	Mitigation at this intersection	City/Port	N/A	Outside of GoPort Project area.

7SGSW, 7SGSE, FITS

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring:		GoPort	Notes (2018 GoPort Technical Studies
•		Schedule	Responsibility	Project	References to Mitigation Measures)
	 Optimize signal timing (i.e., increase the traffic signal cycle length to 80 seconds and adjust the allocation of green time for each intersection approach) for the AM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements. 	may be required by Year 2025. Investigation of the need for this mitigation shall be studied in 2025 and every three years thereafter until 2035 or until the mitigation measure is implemented, whichever occurs first.			
	 Mitigation Measure 3.16- 31: 12th Street & Brush Street (#28) Optimize signal timing (i.e., increase the traffic signal cycle length to 120 seconds and adjust the allocation of green time for each intersection approach) for the AM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements. 	Mitigation at this intersection may be required by Year 2023. Investigation of the need for this mitigation shall be studied in 2023 and every three years thereafter until 2035 or until the mitigation measure is implemented, whichever occurs first.	City/Port	N/A	Outside of GoPort Project area.
	12th Street & Castro Street (#29). See Mitigation Measure 3.16-4 above.	,			
	 Mitigation Measure 3.16- 32: Powell Street & Hollis Street (#37) Provide protected plus permitted traffic signal phasing for the northbound and southbound Hollis Street movements. Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for both the AM and PM peak hours. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. 	Mitigation at this intersection may be required by Year 2028. Investigation of the need for this mitigation shall be studied in	City/Port	N/A	Outside of GoPort Project area.

7SGSW and 7SGSE

7SGSW, 7SGSE, FITS

7SGSW and FITS

7SGSE and FITS

FITS

7SGSW

7SGSE

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring:		GoPort	Notes (2018 GoPort Technical Studies			
Environmental Impact		Schedule	Responsibility	Project	References to Mitigation Measures)			
	To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Emeryville's Transportation Engineering Division for review and approval.	2028 and every three years thereafter until 2035 or until the mitigation						
	The project sponsor shall fund, prepare, and install the approved plans and improvements.	measure is implemented, whichever occurs first.						
	Mitigation Measure 3.16- 33: Powell Street/Stanford Avenue & San Pablo Avenue (#38)	Mitigation at this intersection	City/Port	N/A	Outside of GoPort Project area.			
	• Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the AM peak hour.	by Year 2021. Investigation of	estigation of need for this gation shall studied in 1 and every e years reafter until					
	• Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group.	the need for this mitigation shall						
	To implement this measure, the project sponsor shall submit plans be studied specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval.	be studied in 2021 and every three years thereafter until 2035 or until the mitigation measure is implemented, whichever occurs first.						
	The project sponsor shall fund, prepare, and install the approved plans and improvements.							
4. Four roadway segments of the Congestion Management Program (CMP) would a) degrade to LOS F; or b) increase the V/C ratio by more than three percent for a roadway segment that would operate at LOS F without the project (Year 2035).	See above for Mitigation Measure 4.3-4							
Planning Related Non- CEQA Issues Queuing	Recommended Measures (not required by CEQA) The following improvements are recommended to accommodate the anticipated queues:	At issuance of first Certificate of Occupancy (CO)	City/Port	N/A				

7SGSW and 7SGSE

7SGSW, 7SGSE, FITS

7SGSW and FITS

7SGSE and FITS

FITS

7SGSW

7SGSE

		3.51.1			
		Mitigation Implementation/ Monitoring:	GoPort	Notes	
Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	(2018 GoPort Technical Studies References to Mitigation Measures)
Existing Plus Project: The project would result in exceedance of available storage capacity at only the following locations: Northbound left-turn at W. Grand Avenue & Maritime Street (#1) - PM peak hour Westbound left-turn at 7th Street & Maritime Street (#10) – AM & PM peak hours Eastbound left-turn at 7th Street & I-880 northbound off-ramp (#12) – PM peak hour	 W. Grand Avenue & Maritime Street (#1). Extend the northbound left-turn storage length to 475 feet; while providing a minimum of 100 feet storage length for the southbound left-turn movement at the Burma Road and Maritime Street intersection (#46). 7th Street & Maritime Street (#10). Extend the westbound left-turn storage length to 320 feet by removing a portion of the existing center median. 7th Street & I-880 northbound off-ramp (#12). Convert one of the existing eastbound through lane to an exclusive left-turn lane to provide two left-turn lanes, and one through lane. 				
Year 2020 cumulative conditions: Similar to Existing plus Project conditions, the Project would result in exceedance of available storage at the same three intersections: Northbound left-turn at W. Grand Avenue & Maritime Street (#1) - PM peak hour Westbound left-turn at 7th Street & Maritime Street (#10) – AM & PM peak hours Eastbound and southbound left-turn at 7th Street & I-880 northbound off-ramp (#12) – PM peak hour	Recommended Measures (not required by CEQA) The following improvements are recommended to accommodate the anticipated queues: W. Grand Avenue & Maritime Street (#1). Widen Maritime Street to provide two northbound left-turn lanes at the intersection. Th Street & Maritime Street (#10). Extend the westbound left-turn storage length to 320 feet by removing a portion of the existing center median. Th Street & I-880 northbound off-ramp (#12). Convert one of the existing eastbound through lane to an exclusive left-turn lane to provide two left-turn lanes, and one through lane; and extend the southbound left-turn storage pocket to 250 feet by removing a portion of the existing center median.	At issuance of first Certificate of Occupancy (CO) or 2020, whichever is later	City/Port	N/A	

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Im Monite Schedule		GoPort Project	Notes (2018 GoPort Technical Studies References to Mitigation Measures)
Utilities					,
1. Exceed wastewater treatment requirements of the applicable Regional Water Quality Control Board?	See above for SCA HYD-4 (Hydrology and Water Quality section)				
2. Require or result in the construction of new water or wastewater treatment facilities or expansion of existing facilities, the construction of which could cause significant environmental effects?	SCA UTL-3: Underground Utilities: The project applicant shall submit plans for review and approval by the Building Services Division and the Public Works Agency, and other relevant agencies as appropriate, that show all new electric and telephone facilities; fire alarm conduits; street light wiring; and other wiring, conduits, and similar facilities placed underground. The new facilities shall be placed underground along the project applicant's street frontage and from the project applicant's structures to the point of service. The plans shall show all electric, telephone, water service, fire water service, cable, and fire alarm facilities installed in accordance with standard specifications of the serving utilities.	Prior to issuance of a building permit.	City/Port	7SGSW 7GSSE FITS	Applies to design phase only.
	 SCA UTL-5: Improvements in the Public Right-of Wav (Specific): Final building and public improvement plans submitted to the Building Services Division shall include the following components: Examples include: a) Install additional standard City of Oakland streetlights. b) Remove and replace any existing driveway that will not be used for access to the property with new concrete sidewalk, curb and gutter. c) Reconstruct drainage facility to current City standard. d) Provide separation between sanitary sewer and water lines to comply with current City of Oakland and Alameda Health Department standards. e) Construct wheelchair ramps that comply with Americans with Disability Act requirements and current City Standards. f) Remove and replace deficient concrete sidewalk, curb and gutter within property frontage. g) Provide adequate fire department access and water supply, including, but not limited to currently adopted fire codes and standards. 	Approved prior to the issuance of a grading or building permit.	City/Port	7SGSW 7GSSE FITS	Applies to design phase only.
	SCA UTL-6: Payment for Public Improvements: The project applicant shall pay for and install public improvements made necessary by the project including damage caused by construction activity.	Prior to issuance of a final inspection of the building permit.	City/Port	7SGSW 7SGSE FITS	Applies to Contractor. Applies to all GoPort Projects, including if damage is caused.

Environmental Impact		Mitigation Implementation/ Monitoring:	GoPort	Notes (2018 CaPout Technical Studies	
	Standard Conditions of Approval/Mitigation Measures	Schedule	Responsibility	Project	(2018 GoPort Technical Studies References to Mitigation Measures)
3. Have sufficient water supplies available to serve the project from existing entitlements and resources, or are new or expanded entitlements needed?	Mitigation 4.9-4: Individual actions with landscaping requirements of one or more acres shall plumb landscape areas for irrigation with recycled water. As subsequent redevelopment activities are designed, the City and Port would require that activities of a certain magnitude shall include a reclaimed landscaping irrigation system. The City and Port would make this a condition of approval for private actions that require such approval and would include reclaimed landscape water systems in the design of their own public projects.	Prior to issuance of a building permit or other construction-related permit.	City/Port	7SGSW 7SGSE	Applies to design phase only.
	Mitigation 4.9-5: Individual buildings with gross floor area exceeding 10,000 square feet shall install dual plumbing for both potable and recycled water, unless determined to be infeasible by the approving agency (City or Port).	Prior to issuance of a building permit or other construction- related permit.	City/Port	N/A	
	Any major subsequent redevelopment activity that includes total usable floor area within or more building of 10,000 square feet or more would be required to provide a dual plumbing system—one for potable water, and one for reclaimed water. Reclaimed water may be used for certain industrial uses, and for landscape irrigation, toilet flushing, and other appropriate purposes.				
	Mitigation 4.9-6: Site design shall facilitate use of recycled water and shall comply with requirements of CCR Title 22 regarding prohibitions of site run-off to surface waters. When subsequent redevelopment activities are required to include reclaimed water in their design, the City and Port would ensure that requirements of Title 22 intended to protect the environment are reflected in that design, including prohibitions against run-off to surface waters. The City, Port, and proponents of subsequent redevelopment activities should coordinate these efforts with the reclaimed water supplier, EBMUD.	Prior to issuance of a building permit or other construction-related permit.	City/Port	7SGSW 7SGSE	Applies to design phase only for landscaping irrigation.
	 SCA UTL-1a: Compliance with the Green Building Ordinance, OMC Chapter 18.02: (Note: Final details for text highlighted in gray below to be provided upon issuance of a permit) Prior to issuance of a demolition, grading, or building permit The applicant shall comply with the requirements of the California Green Building Standards (CALGreen) mandatory measures and the applicable requirements of the Green Building Ordinance, OMC Chapter 18.02. a) The following information shall be submitted to the Building Services Division for review and approval with the application for a building permit: 	Prior to issuance of a demolition, grading, or building permit; or during construction or after construction as specified in SCA UTL-1a or UTL-1b.	City/Port	FITS	Applies to both design phase and contractor relative to the Traffic Management Center/Emergency Operations Center (TMC/EOC)

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE 7SGSW and FITS 7SGSW 7SGSE N/A

Environmental Impact	Standard Conditions of Approval/Mitigation Magazines	Mitigation Implementation/ Monitoring:		GoPort	Notes (2018 GoPort Technical Studies
Environmental Impact	Standard Conditions of Approval/Willigation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
Environmental Impact	i. Documentation showing compliance with Title 24 of the 2008 California Building Energy Efficiency Standards. ii. Completed copy of the final green building checklist approved during the review of the Planning and Zoning permit. iii. Copy of the Unreasonable Hardship Exemption, if granted, during the review of the Planning and Zoning permit. iv. Permit plans that show, in general notes, detailed design drawings, and specifications as necessary, compliance with the items listed in subsection (b) below. v. Copy of the signed statement by the Green Building Certifier approved during the review of the Planning and Zoning permit that the project complied with the requirements of the Green Building Ordinance. vi. Signed statement by the Green Building Certifier that the project still complies with the requirements of the Green Building Ordinance, unless an Unreasonable Hardship Exemption was granted during the review of the Planning and Zoning permit. vii. Other documentation as deemed necessary by the City to demonstrate compliance with the Green Building Ordinance. b) The set of plans in subsection (a) shall demonstrate compliance with the following: i. CALGreen mandatory measures. ii. All pre-requisites per the LEED / GreenPoint Rated checklist approved during the review of the Planning and Zoning permit, or, if applicable, all the green building measures approved as part of the Unreasonable Hardship Exemption granted during the review of the	Schedule	Responsibility		References to Mitigation
	Planning and Zoning permit. iii. Insert green building point level/certification requirement: (See Green Building Summary Table) per the appropriate checklist approved during the Planning entitlement process. iv. All green building points identified on the checklist approved during review of the Planning and Zoning permit, unless a Request for Revision Plan-check application is submitted and approved by the Planning and Zoning Division that shows the previously approved points that will be eliminated or substituted. v. The required green building point minimums in the appropriate credit categories.				

During construction

The applicant shall comply with the applicable requirements CALGreen and the Green Building Ordinance, Chapter 18.02.

- a) The following information shall be submitted to the Building Inspections Division of the Building Services Division for review and approval:
 - Completed copies of the green building checklists approved during the review of the Planning and Zoning permit and during the review of the building permit.
 - ii. Signed statement(s) by the Green Building Certifier during all relevant phases of construction that the project complies with the requirements of the Green Building Ordinance.
 - *iii.* Other documentation as deemed necessary by the City to demonstrate compliance with the Green Building Ordinance.

After construction, as specified below

Within sixty (60) days of the final inspection of the building permit for the project, the Green Building Certifier shall submit the appropriate documentation to Build It Green/Green Building Certification Institute and attain the minimum certification/point level identified in subsection (a) above. Within one year of the final inspection of the building permit for the project, the applicant shall submit to the Planning and Zoning Division the Certificate from the organization listed above demonstrating certification and compliance with the minimum point/certification level noted above.

SCA UTL-1b: Compliance with the Green Building Ordinance, OMC Chapter 18.02, for Building and Landscape Projects Using the StopWaste.Org Small Commercial or Bay Friendly Basic Landscape Checklist

Prior to issuance of a building permit

The applicant shall comply with the requirements of the California Green Building Standards (CALGreen) mandatory measures and the applicable requirements of the Green Building Ordinance, (OMC Chapter 18.02.) for projects using the StopWaste.Org Small Commercial or Bay Friendly Basic Landscape Checklist.

- a) The following information shall be submitted to the Building Services
 Division for review and approval with application for a Building permit:
 - Documentation showing compliance with the 2008 Title 24, California Building Energy Efficiency Standards.
 - ii. Completed copy of the green building checklist approved during the review of a Planning and Zoning permit.
 - iii. Permit plans that show in general notes, detailed design drawings and specifications as necessary compliance with the items listed in subsection (b) below.

7SGSW, 7SGSE, FITS 7SGSW and 7SGSE 7SGSW and FITS 7SGSW 7SGSE N/A

Environmental Impact	Standard Conditions of Approval/Mitigation Measures		GoPort	Notes (2018 GoPort Technical Studies	
	Standard Conditions of Approvar/Midgation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	 iv. Other documentation to prove compliance. b) The set of plans in subsection (a) shall demonstrate compliance with the following: i. CALGreen mandatory measures. ii. All applicable green building measures identified on the StopWaste.Org checklist approved during the review of a Planning and Zoning permit, or submittal of a Request for Revision Plancheck application that shows the previously approved points that will be eliminated or substituted. During construction The applicant shall comply with the applicable requirements of CALGreen and Green Building Ordinance, Chapter 18.02 for projects using the StopWaste.Org Small Commercial or Bay Friendly Basic Landscape Checklist. a) The following information shall be submitted to the Building Inspections Division for review and approval: i. Completed copy of the green building checklists approved during review of the Planning and Zoning permit and during the review of the Building permit. ii. Other documentation as deemed necessary by the City to demonstrate compliance with the Green Building Ordinance. 				
4. Result in a determination by the wastewater treatment provider, which serves or may serve the project that it has adequate capacity to serve the project's projected demand in addition to the provider's existing commitments?	See above for SCA HYD-4 (Hydrology and Water Quality section)				
5. Be served by a landfill with sufficient permitted capacity to accommodate the project's solid waste disposal needs?	SCA UTL-2: Waste Reduction and Recycling: The project applicant will submit a Construction & Demolition Waste Reduction and Recycling Plan (WRRP) and an Operational Diversion Plan (ODP) for review and approval by the Public Works Agency. Prior to issuance of demolition, grading, or building permit	Prior to issuance of demolition, grading, or building permit; or ongoing as	City/Port	7SGSW 7SGSE FITS	Applies to Contractor.

Environmental Impact	Standard Conditions of Approval/Mitigation Measures		GoPort	Notes (2018 GoPort Technical Studies	
Environmental impact	Standard Conditions of Approvar/Midgation Measures	Schedule	Responsibility	Project	References to Mitigation Measures)
	Chapter 15.34 of the Oakland Municipal Code outlines requirements for reducing waste and optimizing construction and demolition (C&D) recycling. Affected projects include all new construction, renovations/alterations/modifications with construction values of \$50,000 or more (except R-3), and all demolition (including soft demo). The WRRP must specify the methods by which the development will divert C&D debris waste generated by the proposed project from landfill disposal in accordance with current City requirements. Current standards, FAQs, and forms are available at http://www2.oaklandnet.com/Government/o/PWA/o/FE/s/GAR/OAK024368 or in the Green Building Resource Center. After approval of the plan, the project applicant shall implement the plan. **Ongoing** The ODP will identify how the project complies with the Recycling Space Allocation Ordinance, (Chapter 17.118 of the Oakland Municipal Code), including capacity calculations, and specify the methods by which the development will meet the current diversion of solid waste generated by operation of the proposed project from landfill disposal in accordance with current City requirements. The proposed program shall be in implemented and maintained for the duration of the proposed activity or facility. Changes to the plan may be re-submitted to the Environmental Services Division of the Public Works Agency for review and approval. Any incentive programs shall remain fully operational as long as residents and businesses exist at the project site.	specified in SCA ULT-2.			
	Mitigation: 4.9-7: To the maximum extent feasible, the City and Port shall jointly participate in a deconstruction program to capture materials and recycle them into the construction market. Substantial quantities of construction debris would be generated by the removal of structures at the OARB, in both the Gateway and Port development areas. Some of the buildings span both development areas, and coordination between the Port and City is critical in reducing the amount of solid waste disposal that occurs in this sub-district. The City and Port would jointly plan, implement, and operate a program whereby buildings would be deconstructed, rather than demolished, and the resulting material would be recycled to the construction market as practicable. Material for recycling may include, and is not limited to, timbers and siding, ceramic fixtures, metal, and copper wiring. The City and Port may elect to partner with local job-training bridge programs to provide construction training opportunities to Oakland residents through their deconstruction program.	Prior to issuance of a demolition permit	City/Port	N/A	

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring:		GoPort	Notes (2018 GoPort Technical Studies
		Schedule	Responsibility	Project	References to Mitigation Measures)
	Mitigation 4.9-8: Concrete and asphalt removed during demolition/construction shall be crushed on site or at a near site location and reused in redevelopment or recycled to the construction market. Foundation and paving removal would generate substantial debris, and the City and Port would ensure these materials are crushed and recycled. As a first preference, these materials should be re-used on-site; as a second preference, they would be sold to the construction market. The City and Port would make every effort practicable to avoid disposal to landfill of this material. This mitigation measure may itself result in impacts to the environment relative to noise and air quality. These impacts are discussed in Sections 4.4: Air Quality, and 4.15: Noise.	On-going, during construction	City/Port	7SGSW 7SGSE	Applies to Contractor.
6. Comply with federal, State, and local statutes and regulations related to solid waste?7. Would the project violate applicable federal, state and local statutes and regulations	See above for SCA UTL-2 See above for SCA UTL-1				
relating to energy standards?					

Environmental Impact	Standard Conditions of Approval/Mitigation Measures	Mitigation Implementation/ Monitoring:		GoPort	Notes (2018 GoPort Technical Studies
		Schedule	Responsibility	Project	References to Mitigation Measures)
8. Would the project result in a determination by the energy provider which serves or may serve the project that it does not have adequate capacity to serve the project's projected demand in addition to the providers' existing commitments and require or result in construction of new energy facilities or expansion of existing facilities, construction of which could cause significant environmental effects?	See above for SCA UTL-1				